APPENDIX I

BASIC FREEWAY SEGMENT ANALYSIS

APPENDIX I-I

EXISTING TRAFFIC CONDITIONS

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*SR-22 EB*
Agency or Company	*LLG*	From/To	*East of Studebaker Rd*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*AM Peak Hour*	Analysis Year	*Existing*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs				
Volume, V	*4209*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length Up/Down %	*mi*

Calculate Flow Adjustments			
f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs			Calc Speed Adj and FFS		
Lane Width		ft			
Rt-Side Lat. Clearance		ft	f_{LW}		mph
Number of Lanes, N	*2*		f_{LC}		mph
Total Ramp Density, TRD		ramps/mi	TRD Adjustment		mph
FFS (measured)	*65.0*	mph	FFS	*65.0*	mph
Base free-flow Speed, BFFS		mph			

LOS and Performance Measures			Design (N)		
Operational (LOS)			Design (N)		
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*2237*	pc/h/ln	Design LOS		
			v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)		pc/h/ln
S	*55.1*	mph	S		mph
D = v_p / S	*40.6*	pc/mi/ln	D = v_p / S		pc/mi/ln
LOS	*E*		Required Number of Lanes, N		

Glossary		Factor Location	
N - Number of lanes	S - Speed	E_R - Exhibits 11-10, 11-12	f_{LW} - Exhibit 11-8
V - Hourly volume	D - Density	E_T - Exhibits 11-10, 11-11, 11-13	f_{LC} - Exhibit 11-9
v_p - Flow rate	FFS - Free-flow speed	f_p - Page 11-18	TRD - Page 11-11
LOS - Level of service	BFFS - Base free-flow speed	LOS, S, FFS, v_p - Exhibits 11-2, 11-3	
DDHV - Directional design hour volume			

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 1:54 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*SR-22 WB*
Agency or Company	*LLG*	From/To	*East of Studebaker Rd*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*AM Peak Hour*	Analysis Year	*Existing*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*3193*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length Up/Down %	*mi*

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs			Calc Speed Adj and FFS		
Lane Width		ft			
Rt-Side Lat. Clearance		ft	f_{LW}		mph
Number of Lanes, N	*2*		f_{LC}		mph
Total Ramp Density, TRD		ramps/mi	TRD Adjustment		mph
FFS (measured)	*65.0*	mph	FFS	*65.0*	mph
Base free-flow Speed, BFFS		mph			

LOS and Performance Measures			Design (N)	
Operational (LOS)			Design (N)	
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*1697*	pc/h/ln	Design LOS	
			v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	pc/h/ln
S	*63.7*	mph	S	mph
D = v_p / S	*26.6*	pc/mi/ln	D = v_p / S	pc/mi/ln
LOS	*D*		Required Number of Lanes, N	

Glossary		Factor Location	
N - Number of lanes	S - Speed	E_R - Exhibits 11-10, 11-12	f_{LW} - Exhibit 11-8
V - Hourly volume	D - Density	E_T - Exhibits 11-10, 11-11, 11-13	f_{LC} - Exhibit 11-9
v_p - Flow rate	FFS - Free-flow speed	f_p - Page 11-18	TRD - Page 11-11
LOS - Level of service	BFFS - Base free-flow speed	LOS, S, FFS, v_p - Exhibits 11-2, 11-3	
DDHV - Directional design hour volume			

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 1:55 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*I-605 NB*
Agency or Company	*LLG*	From/To	*South of Katella Ave*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*AM Peak Hour*	Analysis Year	*Existing*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*6401*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length Up/Down %	*mi*

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs

Lane Width		ft
Rt-Side Lat. Clearance		ft
Number of Lanes, N	*6*	
Total Ramp Density, TRD		ramps/mi
FFS (measured)	*65.0*	mph
Base free-flow Speed, BFFS		mph

Calc Speed Adj and FFS

f_{LW}		mph
f_{LC}		mph
TRD Adjustment		mph
FFS	*65.0*	mph

LOS and Performance Measures

Operational (LOS)

v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*1134*	pc/h/ln
S	*65.0*	mph
D = v_p / S	*17.4*	pc/mi/ln
LOS	*B*	

Design (N)

Design (N)

Design LOS		
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)		pc/h/ln
S		mph
D = v_p / S		pc/mi/ln
Required Number of Lanes, N		

Glossary

N - Number of lanes
V - Hourly volume
v_p - Flow rate
LOS - Level of service
S - Speed
D - Density
FFS - Free-flow speed
BFFS - Base free-flow speed
DDHV - Directional design hour volume

Factor Location

E_R - Exhibits 11-10, 11-12
E_T - Exhibits 11-10, 11-11, 11-13
f_p - Page 11-18
LOS, S, FFS, v_p - Exhibits 11-2, 11-3
f_{LW} - Exhibit 11-8
f_{LC} - Exhibit 11-9
TRD - Page 11-11

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 1:57 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*I-605 SB*
Agency or Company	*LLG*	From/To	*South of Katella Ave*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*AM Peak Hour*	Analysis Year	*Existing*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*4670*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length	*mi*
			Up/Down %	

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs

Lane Width		ft
Rt-Side Lat. Clearance		ft
Number of Lanes, N	*6*	
Total Ramp Density, TRD		ramps/mi
FFS (measured)	*65.0*	mph
Base free-flow Speed, BFFS		mph

Calc Speed Adj and FFS

f_{LW}		mph
f_{LC}		mph
TRD Adjustment		mph
FFS	*65.0*	mph

LOS and Performance Measures

Operational (LOS)

v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*827*	pc/h/ln
S	*65.0*	mph
D = v_p / S	*12.7*	pc/mi/ln
LOS	*B*	

Design (N)

Design (N)

Design LOS		
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)		pc/h/ln
S		mph
D = v_p / S		pc/mi/ln
Required Number of Lanes, N		

Glossary

N - Number of lanes
V - Hourly volume
v_p - Flow rate
LOS - Level of service
S - Speed
D - Density
FFS - Free-flow speed
BFFS - Base free-flow speed
DDHV - Directional design hour volume

Factor Location

E_R - Exhibits 11-10, 11-12
E_T - Exhibits 11-10, 11-11, 11-13
f_p - Page 11-18
LOS, S, FFS, v_p - Exhibits 11-2, 11-3
f_{LW} - Exhibit 11-8
f_{LC} - Exhibit 11-9
TRD - Page 11-11

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 1:59 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*I-405 NB*
Agency or Company	*LLG*	From/To	*Bellflower Blvd/Woodruff Ave*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*AM Peak Hour*	Analysis Year	*Existing*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*9152*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length	*mi*
			Up/Down %	

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs

Lane Width		ft
Rt-Side Lat. Clearance		ft
Number of Lanes, N	*6*	
Total Ramp Density, TRD		ramps/mi
FFS (measured)	*65.0*	mph
Base free-flow Speed, BFFS		mph

Calc Speed Adj and FFS

f_{LW}		mph
f_{LC}		mph
TRD Adjustment		mph
FFS	*65.0*	mph

LOS and Performance Measures

Operational (LOS)

v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*1622*	pc/h/ln
S	*64.3*	mph
D = v_p / S	*25.2*	pc/mi/ln
LOS	*C*	

Design (N)

Design (N)

Design LOS	
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	pc/h/ln
S	mph
D = v_p / S	pc/mi/ln
Required Number of Lanes, N	

Glossary

N - Number of lanes
V - Hourly volume
v_p - Flow rate
LOS - Level of service
S - Speed
D - Density
FFS - Free-flow speed
BFFS - Base free-flow speed
DDHV - Directional design hour volume

Factor Location

E_R - Exhibits 11-10, 11-12
E_T - Exhibits 11-10, 11-11, 11-13
f_p - Page 11-18
LOS, S, FFS, v_p - Exhibits 11-2, 11-3
f_{LW} - Exhibit 11-8
f_{LC} - Exhibit 11-9
TRD - Page 11-11

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 2:01 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*I-405 NB*
Agency or Company	*LLG*	From/To	*Woodruff Ave/Palo Verde Ave*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*AM Peak Hour*	Analysis Year	*Existing*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*8977*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length Up/Down %	*mi*

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs

Lane Width		ft
Rt-Side Lat. Clearance		ft
Number of Lanes, N	*6*	
Total Ramp Density, TRD		ramps/mi
FFS (measured)	*65.0*	mph
Base free-flow Speed, BFFS		mph

Calc Speed Adj and FFS

f_{LW}		mph
f_{LC}		mph
TRD Adjustment		mph
FFS	*65.0*	mph

LOS and Performance Measures

Operational (LOS)

v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*1591*	pc/h/ln
S	*64.5*	mph
D = v_p / S	*24.7*	pc/mi/ln
LOS	*C*	

Design (N)

Design (N)

Design LOS	
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	pc/h/ln
S	mph
D = v_p / S	pc/mi/ln
Required Number of Lanes, N	

Glossary

N - Number of lanes
V - Hourly volume
v_p - Flow rate
LOS - Level of service
S - Speed
D - Density
FFS - Free-flow speed
BFFS - Base free-flow speed
DDHV - Directional design hour volume

Factor Location

E_R - Exhibits 11-10, 11-12
E_T - Exhibits 11-10, 11-11, 11-13
f_p - Page 11-18
LOS, S, FFS, v_p - Exhibits 11-2, 11-3
f_{LW} - Exhibit 11-8
f_{LC} - Exhibit 11-9
TRD - Page 11-11

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 2:02 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*I-405 NB*
Agency or Company	*LLG*	From/To	*Palo Verde Ave/Studebaker Rd*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*AM Peak Hour*	Analysis Year	*Existing*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*9326*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length Up/Down %	*mi*

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs

Lane Width		ft
Rt-Side Lat. Clearance		ft
Number of Lanes, N	*6*	
Total Ramp Density, TRD		ramps/mi
FFS (measured)	*65.0*	mph
Base free-flow Speed, BFFS		mph

Calc Speed Adj and FFS

f_{LW}		mph
f_{LC}		mph
TRD Adjustment		mph
FFS	*65.0*	mph

LOS and Performance Measures

Operational (LOS)

v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*1653*	pc/h/ln
S	*64.1*	mph
D = v_p / S	*25.8*	pc/mi/ln
LOS	*C*	

Design (N)

Design (N)

Design LOS		
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)		pc/h/ln
S		mph
D = v_p / S		pc/mi/ln
Required Number of Lanes, N		

Glossary

N - Number of lanes
V - Hourly volume
v_p - Flow rate
LOS - Level of service
S - Speed
D - Density
FFS - Free-flow speed
BFFS - Base free-flow speed
DDHV - Directional design hour volume

Factor Location

E_R - Exhibits 11-10, 11-12
E_T - Exhibits 11-10, 11-11, 11-13
f_p - Page 11-18
LOS, S, FFS, v_p - Exhibits 11-2, 11-3
f_{LW} - Exhibit 11-8
f_{LC} - Exhibit 11-9
TRD - Page 11-11

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 2:03 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*I-405 NB*
Agency or Company	*LLG*	From/To	*South of Studebaker Rd*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*AM Peak Hour*	Analysis Year	*Existing*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*9117*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length Up/Down %	*mi*

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs			Calc Speed Adj and FFS		
Lane Width		ft			
Rt-Side Lat. Clearance		ft	f_{LW}		mph
Number of Lanes, N	*5*		f_{LC}		mph
Total Ramp Density, TRD		ramps/mi	TRD Adjustment		mph
FFS (measured)	*65.0*	mph	FFS	*65.0*	mph
Base free-flow Speed, BFFS		mph			

LOS and Performance Measures			Design (N)	
Operational (LOS)			Design (N)	
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*1939*	pc/h/ln	Design LOS	
			v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	pc/h/ln
S	*60.9*	mph	S	mph
D = v_p / S	*31.8*	pc/mi/ln	D = v_p / S	pc/mi/ln
LOS	*D*		Required Number of Lanes, N	

Glossary		Factor Location	
N - Number of lanes	S - Speed	E_R - Exhibits 11-10, 11-12	f_{LW} - Exhibit 11-8
V - Hourly volume	D - Density	E_T - Exhibits 11-10, 11-11, 11-13	f_{LC} - Exhibit 11-9
v_p - Flow rate	FFS - Free-flow speed	f_p - Page 11-18	TRD - Page 11-11
LOS - Level of service	BFFS - Base free-flow speed	LOS, S, FFS, v_p - Exhibits 11-2, 11-3	
DDHV - Directional design hour volume			

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 2:04 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*I-405 SB*
Agency or Company	*LLG*	From/To	*Bellflower Blvd/Woodruff Ave*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*AM Peak Hour*	Analysis Year	*Existing*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*8234*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length	*mi*
			Up/Down %	

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs

Lane Width		ft
Rt-Side Lat. Clearance		ft
Number of Lanes, N	*6*	
Total Ramp Density, TRD		ramps/mi
FFS (measured)	*65.0*	mph
Base free-flow Speed, BFFS		mph

Calc Speed Adj and FFS

f_{LW}		mph
f_{LC}		mph
TRD Adjustment		mph
FFS	*65.0*	mph

LOS and Performance Measures

Operational (LOS)

v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*1459*	pc/h/ln
S	*65.0*	mph
D = v_p / S	*22.5*	pc/mi/ln
LOS	*C*	

Design (N)

Design (N)

Design LOS		
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)		pc/h/ln
S		mph
D = v_p / S		pc/mi/ln
Required Number of Lanes, N		

Glossary

N - Number of lanes
V - Hourly volume
v_p - Flow rate
LOS - Level of service
S - Speed
D - Density
FFS - Free-flow speed
BFFS - Base free-flow speed
DDHV - Directional design hour volume

Factor Location

E_R - Exhibits 11-10, 11-12
E_T - Exhibits 11-10, 11-11, 11-13
f_p - Page 11-18
LOS, S, FFS, v_p - Exhibits 11-2, 11-3
f_{LW} - Exhibit 11-8
f_{LC} - Exhibit 11-9
TRD - Page 11-11

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 2:12 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*I-405 SB*
Agency or Company	*LLG*	From/To	*Woodruff Ave/Palo Verde Ave*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*AM Peak Hour*	Analysis Year	*Existing*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*8077*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length Up/Down %	*mi*

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs

Lane Width		ft
Rt-Side Lat. Clearance		ft
Number of Lanes, N	*5*	
Total Ramp Density, TRD		ramps/mi
FFS (measured)	*65.0*	mph
Base free-flow Speed, BFFS		mph

Calc Speed Adj and FFS

f_{LW}		mph
f_{LC}		mph
TRD Adjustment		mph
FFS	*65.0*	mph

LOS and Performance Measures

Operational (LOS)

v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*1717*	pc/h/ln
S	*63.6*	mph
D = v_p / S	*27.0*	pc/mi/ln
LOS	*D*	

Design (N)

Design (N)

Design LOS		
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)		pc/h/ln
S		mph
D = v_p / S		pc/mi/ln
Required Number of Lanes, N		

Glossary

N - Number of lanes
V - Hourly volume
v_p - Flow rate
LOS - Level of service
S - Speed
D - Density
FFS - Free-flow speed
BFFS - Base free-flow speed
DDHV - Directional design hour volume

Factor Location

E_R - Exhibits 11-10, 11-12
E_T - Exhibits 11-10, 11-11, 11-13
f_p - Page 11-18
LOS, S, FFS, v_p - Exhibits 11-2, 11-3
f_{LW} - Exhibit 11-8
f_{LC} - Exhibit 11-9
TRD - Page 11-11

Copyright © 2016 University of Florida, All Rights Reserved

HCS 2010™ Version 6.80 Generated: 1/18/2017 2:13 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*I-405 SB*
Agency or Company	*LLG*	From/To	*Palo Verde Ave/Studebaker Rd*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*AM Peak Hour*	Analysis Year	*Existing*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*8391*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length Up/Down %	*mi*

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs

Lane Width		ft
Rt-Side Lat. Clearance		ft
Number of Lanes, N	*6*	
Total Ramp Density, TRD		ramps/mi
FFS (measured)	*65.0*	mph
Base free-flow Speed, BFFS		mph

Calc Speed Adj and FFS

f_{LW}		mph
f_{LC}		mph
TRD Adjustment		mph
FFS	*65.0*	mph

LOS and Performance Measures

Operational (LOS)

v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*1487*	pc/h/ln
S	*64.9*	mph
D = v_p / S	*22.9*	pc/mi/ln
LOS	*C*	

Design (N)

Design (N)

Design LOS	
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	pc/h/ln
S	mph
D = v_p / S	pc/mi/ln
Required Number of Lanes, N	

Glossary

N - Number of lanes
V - Hourly volume
v_p - Flow rate
LOS - Level of service
S - Speed
D - Density
FFS - Free-flow speed
BFFS - Base free-flow speed
DDHV - Directional design hour volume

Factor Location

E_R - Exhibits 11-10, 11-12
E_T - Exhibits 11-10, 11-11, 11-13
f_p - Page 11-18
LOS, S, FFS, v_p - Exhibits 11-2, 11-3
f_{LW} - Exhibit 11-8
f_{LC} - Exhibit 11-9
TRD - Page 11-11

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 2:13 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*I-405 SB*
Agency or Company	*LLG*	From/To	*South of Studebaker Rd*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*AM Peak Hour*	Analysis Year	*Existing*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*8202*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length	*mi*
			Up/Down %	

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs

Lane Width		ft
Rt-Side Lat. Clearance		ft
Number of Lanes, N	*6*	
Total Ramp Density, TRD		ramps/mi
FFS (measured)	*65.0*	mph
Base free-flow Speed, BFFS		mph

Calc Speed Adj and FFS

f_{LW}		mph
f_{LC}		mph
TRD Adjustment		mph
FFS	*65.0*	mph

LOS and Performance Measures

Operational (LOS)

v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*1453*	pc/h/ln
S	*65.0*	mph
D = v_p / S	*22.4*	pc/mi/ln
LOS	*C*	

Design (N)

Design (N)

Design LOS	
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	pc/h/ln
S	mph
D = v_p / S	pc/mi/ln
Required Number of Lanes, N	

Glossary

N - Number of lanes
V - Hourly volume
v_p - Flow rate
LOS - Level of service
S - Speed
D - Density
FFS - Free-flow speed
BFFS - Base free-flow speed
DDHV - Directional design hour volume

Factor Location

E_R - Exhibits 11-10, 11-12
E_T - Exhibits 11-10, 11-11, 11-13
f_p - Page 11-18
LOS, S, FFS, v_p - Exhibits 11-2, 11-3
f_{LW} - Exhibit 11-8
f_{LC} - Exhibit 11-9
TRD - Page 11-11

Copyright © 2016 University of Florida, All Rights Reserved

HCS 2010™ Version 6.80 Generated: 1/18/2017 2:14 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*SR-22 EB*
Agency or Company	*LLG*	From/To	*East of Studebaker Rd*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*PM Peak Hour*	Analysis Year	*Existing*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*3944*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length Up/Down %	*mi*

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs

Lane Width		ft
Rt-Side Lat. Clearance		ft
Number of Lanes, N	*2*	
Total Ramp Density, TRD		ramps/mi
FFS (measured)	*65.0*	mph
Base free-flow Speed, BFFS		mph

Calc Speed Adj and FFS

f_{LW}		mph
f_{LC}		mph
TRD Adjustment		mph
FFS	*65.0*	mph

LOS and Performance Measures

Operational (LOS)

v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*2097*	pc/h/ln
S	*58.1*	mph
D = v_p / S	*36.1*	pc/mi/ln
LOS	*E*	

Design (N)

Design (N)

Design LOS		
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)		pc/h/ln
S		mph
D = v_p / S		pc/mi/ln
Required Number of Lanes, N		

Glossary

N - Number of lanes
V - Hourly volume
v_p - Flow rate
LOS - Level of service
S - Speed
D - Density
FFS - Free-flow speed
BFFS - Base free-flow speed
DDHV - Directional design hour volume

Factor Location

E_R - Exhibits 11-10, 11-12
E_T - Exhibits 11-10, 11-11, 11-13
f_p - Page 11-18
LOS, S, FFS, v_p - Exhibits 11-2, 11-3
f_{LW} - Exhibit 11-8
f_{LC} - Exhibit 11-9
TRD - Page 11-11

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 2:25 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*SR-22 WB*
Agency or Company	*LLG*	From/To	*East of Studebaker Rd*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*PM Peak Hour*	Analysis Year	*Existing*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*4041*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length Up/Down %	*mi*

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs

Lane Width		ft
Rt-Side Lat. Clearance		ft
Number of Lanes, N	*2*	
Total Ramp Density, TRD		ramps/mi
FFS (measured)	*65.0*	mph
Base free-flow Speed, BFFS		mph

Calc Speed Adj and FFS

f_{LW}		mph
f_{LC}		mph
TRD Adjustment		mph
FFS	*65.0*	mph

LOS and Performance Measures

Operational (LOS)

v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*2148*	pc/h/ln
S	*57.1*	mph
D = v_p / S	*37.6*	pc/mi/ln
LOS	*E*	

Design (N)

Design (N)

Design LOS		
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)		pc/h/ln
S		mph
D = v_p / S		pc/mi/ln
Required Number of Lanes, N		

Glossary

N - Number of lanes
V - Hourly volume
v_p - Flow rate
LOS - Level of service
S - Speed
D - Density
FFS - Free-flow speed
BFFS - Base free-flow speed
DDHV - Directional design hour volume

Factor Location

E_R - Exhibits 11-10, 11-12
E_T - Exhibits 11-10, 11-11, 11-13
f_p - Page 11-18
LOS, S, FFS, v_p - Exhibits 11-2, 11-3
f_{LW} - Exhibit 11-8
f_{LC} - Exhibit 11-9
TRD - Page 11-11

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 2:26 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*I-605 NB*
Agency or Company	*LLG*	From/To	*South of Katella Ave*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*PM Peak Hour*	Analysis Year	*Existing*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*7632*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length	*mi*
			Up/Down %	

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs

Lane Width		ft
Rt-Side Lat. Clearance		ft
Number of Lanes, N	*6*	
Total Ramp Density, TRD		ramps/mi
FFS (measured)	*65.0*	mph
Base free-flow Speed, BFFS		mph

Calc Speed Adj and FFS

f_{LW}		mph
f_{LC}		mph
TRD Adjustment		mph
FFS	*65.0*	mph

LOS and Performance Measures

Operational (LOS)

v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*1352*	pc/h/ln
S	*65.0*	mph
D = v_p / S	*20.8*	pc/mi/ln
LOS	*C*	

Design (N)

Design (N)

Design LOS		
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)		pc/h/ln
S		mph
D = v_p / S		pc/mi/ln
Required Number of Lanes, N		

Glossary

N - Number of lanes
V - Hourly volume
v_p - Flow rate
LOS - Level of service
S - Speed
D - Density
FFS - Free-flow speed
BFFS - Base free-flow speed
DDHV - Directional design hour volume

Factor Location

E_R - Exhibits 11-10, 11-12
E_T - Exhibits 11-10, 11-11, 11-13
f_p - Page 11-18
LOS, S, FFS, v_p - Exhibits 11-2, 11-3
f_{LW} - Exhibit 11-8
f_{LC} - Exhibit 11-9
TRD - Page 11-11

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 2:26 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*I-605 SB*
Agency or Company	*LLG*	From/To	*South of Katella Ave*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*PM Peak Hour*	Analysis Year	*Existing*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs				
Volume, V	*5345*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length	*mi*
			Up/Down %	

Calculate Flow Adjustments			
f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs			Calc Speed Adj and FFS		
Lane Width		ft			
Rt-Side Lat. Clearance		ft	f_{LW}		mph
Number of Lanes, N	*6*		f_{LC}		mph
Total Ramp Density, TRD		ramps/mi	TRD Adjustment		mph
FFS (measured)	*65.0*	mph	FFS	*65.0*	mph
Base free-flow Speed, BFFS		mph			

LOS and Performance Measures			Design (N)		
Operational (LOS)			Design (N)		
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*947*	pc/h/ln	Design LOS		
S	*65.0*	mph	v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)		pc/h/ln
D = v_p / S	*14.6*	pc/mi/ln	S		mph
LOS	*B*		D = v_p / S		pc/mi/ln
			Required Number of Lanes, N		

Glossary		Factor Location	
N - Number of lanes	S - Speed	E_R - Exhibits 11-10, 11-12	f_{LW} - Exhibit 11-8
V - Hourly volume	D - Density	E_T - Exhibits 11-10, 11-11, 11-13	f_{LC} - Exhibit 11-9
v_p - Flow rate	FFS - Free-flow speed	f_p - Page 11-18	TRD - Page 11-11
LOS - Level of service	BFFS - Base free-flow speed	LOS, S, FFS, v_p - Exhibits 11-2, 11-3	
DDHV - Directional design hour volume			

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 2:27 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*I-405 NB*
Agency or Company	*LLG*	From/To	*Bellflower Blvd/Woodruff Ave*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*PM Peak Hour*	Analysis Year	*Existing*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*8056*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length Up/Down %	*mi*

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs			Calc Speed Adj and FFS		
Lane Width		ft			
Rt-Side Lat. Clearance		ft	f_{LW}		mph
Number of Lanes, N	*6*		f_{LC}		mph
Total Ramp Density, TRD		ramps/mi	TRD Adjustment		mph
FFS (measured)	*65.0*	mph	FFS	*65.0*	mph
Base free-flow Speed, BFFS		mph			

LOS and Performance Measures			Design (N)	
Operational (LOS)			Design (N)	
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*1427*	pc/h/ln	Design LOS	
			v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	pc/h/ln
S	*65.0*	mph	S	mph
D = v_p / S	*22.0*	pc/mi/ln	D = v_p / S	pc/mi/ln
LOS	*C*		Required Number of Lanes, N	

Glossary		Factor Location	
N - Number of lanes	S - Speed	E_R - Exhibits 11-10, 11-12	f_{LW} - Exhibit 11-8
V - Hourly volume	D - Density	E_T - Exhibits 11-10, 11-11, 11-13	f_{LC} - Exhibit 11-9
v_p - Flow rate	FFS - Free-flow speed	f_p - Page 11-18	TRD - Page 11-11
LOS - Level of service	BFFS - Base free-flow speed	LOS, S, FFS, v_p - Exhibits 11-2, 11-3	
DDHV - Directional design hour volume			

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 2:27 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*I-405 NB*
Agency or Company	*LLG*	From/To	*Woodruff Ave/Palo Verde Ave*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*PM Peak Hour*	Analysis Year	*Existing*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*7902*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length Up/Down %	*mi*

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs

Lane Width		ft
Rt-Side Lat. Clearance		ft
Number of Lanes, N	*6*	
Total Ramp Density, TRD		ramps/mi
FFS (measured)	*65.0*	mph
Base free-flow Speed, BFFS		mph

Calc Speed Adj and FFS

f_{LW}		mph
f_{LC}		mph
TRD Adjustment		mph
FFS	*65.0*	mph

LOS and Performance Measures

Operational (LOS)

v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*1400*	pc/h/ln
S	*65.0*	mph
D = v_p / S	*21.5*	pc/mi/ln
LOS	*C*	

Design (N)

Design (N)

Design LOS	
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	pc/h/ln
S	mph
D = v_p / S	pc/mi/ln
Required Number of Lanes, N	

Glossary

N - Number of lanes
V - Hourly volume
v_p - Flow rate
LOS - Level of service
S - Speed
D - Density
FFS - Free-flow speed
BFFS - Base free-flow speed
DDHV - Directional design hour volume

Factor Location

E_R - Exhibits 11-10, 11-12
E_T - Exhibits 11-10, 11-11, 11-13
f_p - Page 11-18
LOS, S, FFS, v_p - Exhibits 11-2, 11-3
f_{LW} - Exhibit 11-8
f_{LC} - Exhibit 11-9
TRD - Page 11-11

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 2:27 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*I-405 NB*
Agency or Company	*LLG*	From/To	*Palo Verde Ave/Studebaker Rd*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*PM Peak Hour*	Analysis Year	*Existing*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*8209*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length Up/Down %	*mi*

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs

Lane Width		ft
Rt-Side Lat. Clearance		ft
Number of Lanes, N	*6*	
Total Ramp Density, TRD		ramps/mi
FFS (measured)	*65.0*	mph
Base free-flow Speed, BFFS		mph

Calc Speed Adj and FFS

f_{LW}		mph
f_{LC}		mph
TRD Adjustment		mph
FFS	*65.0*	mph

LOS and Performance Measures

Operational (LOS)

v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*1455*	pc/h/ln
S	*65.0*	mph
D = v_p / S	*22.4*	pc/mi/ln
LOS	*C*	

Design (N)

Design (N)

Design LOS	
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	pc/h/ln
S	mph
D = v_p / S	pc/mi/ln
Required Number of Lanes, N	

Glossary

N - Number of lanes
V - Hourly volume
v_p - Flow rate
LOS - Level of service
S - Speed
D - Density
FFS - Free-flow speed
BFFS - Base free-flow speed
DDHV - Directional design hour volume

Factor Location

E_R - Exhibits 11-10, 11-12
E_T - Exhibits 11-10, 11-11, 11-13
f_p - Page 11-18
LOS, S, FFS, v_p - Exhibits 11-2, 11-3
f_{LW} - Exhibit 11-8
f_{LC} - Exhibit 11-9
TRD - Page 11-11

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 2:28 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*I-405 NB*
Agency or Company	*LLG*	From/To	*South of Studebaker Rd*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*PM Peak Hour*	Analysis Year	*Existing*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*8024*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length Up/Down %	*mi*

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs

Lane Width		ft
Rt-Side Lat. Clearance		ft
Number of Lanes, N	*5*	
Total Ramp Density, TRD		ramps/mi
FFS (measured)	*65.0*	mph
Base free-flow Speed, BFFS		mph

Calc Speed Adj and FFS

f_{LW}		mph
f_{LC}		mph
TRD Adjustment		mph
FFS	*65.0*	mph

LOS and Performance Measures

Operational (LOS)

v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*1706*	pc/h/ln
S	*63.7*	mph
D = v_p / S	*26.8*	pc/mi/ln
LOS	*D*	

Design (N)

Design (N)

Design LOS		
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)		pc/h/ln
S		mph
D = v_p / S		pc/mi/ln
Required Number of Lanes, N		

Glossary

N - Number of lanes
V - Hourly volume
v_p - Flow rate
LOS - Level of service
S - Speed
D - Density
FFS - Free-flow speed
BFFS - Base free-flow speed
DDHV - Directional design hour volume

Factor Location

E_R - Exhibits 11-10, 11-12
E_T - Exhibits 11-10, 11-11, 11-13
f_p - Page 11-18
LOS, S, FFS, v_p - Exhibits 11-2, 11-3
f_{LW} - Exhibit 11-8
f_{LC} - Exhibit 11-9
TRD - Page 11-11

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 2:28 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*I-405 SB*
Agency or Company	*LLG*	From/To	*Bellflower Blvd/Woodruff Ave*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*PM Peak Hour*	Analysis Year	*Existing*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*10071*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length Up/Down %	*mi*

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs

Lane Width		ft
Rt-Side Lat. Clearance		ft
Number of Lanes, N	*6*	
Total Ramp Density, TRD		ramps/mi
FFS (measured)	*65.0*	mph
Base free-flow Speed, BFFS		mph

Calc Speed Adj and FFS

f_{LW}		mph
f_{LC}		mph
TRD Adjustment		mph
FFS	*65.0*	mph

LOS and Performance Measures

Operational (LOS)

v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*1785*	pc/h/ln
S	*62.9*	mph
D = v_p / S	*28.4*	pc/mi/ln
LOS	*D*	

Design (N)

Design (N)

Design LOS		
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)		pc/h/ln
S		mph
D = v_p / S		pc/mi/ln
Required Number of Lanes, N		

Glossary

N - Number of lanes
V - Hourly volume
v_p - Flow rate
LOS - Level of service
S - Speed
D - Density
FFS - Free-flow speed
BFFS - Base free-flow speed
DDHV - Directional design hour volume

Factor Location

E_R - Exhibits 11-10, 11-12
E_T - Exhibits 11-10, 11-11, 11-13
f_p - Page 11-18
LOS, S, FFS, v_p - Exhibits 11-2, 11-3
f_{LW} - Exhibit 11-8
f_{LC} - Exhibit 11-9
TRD - Page 11-11

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 2:28 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*I-405 SB*
Agency or Company	*LLG*	From/To	*Woodruff Ave/Palo Verde Ave*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*PM Peak Hour*	Analysis Year	*Existing*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*9879*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length Up/Down %	*mi*

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs

Lane Width		ft
Rt-Side Lat. Clearance		ft
Number of Lanes, N	*5*	
Total Ramp Density, TRD		ramps/mi
FFS (measured)	*65.0*	mph
Base free-flow Speed, BFFS		mph

Calc Speed Adj and FFS

f_{LW}		mph
f_{LC}		mph
TRD Adjustment		mph
FFS	*65.0*	mph

LOS and Performance Measures

Operational (LOS)

v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*2101*	pc/h/ln
S	*58.0*	mph
D = v_p / S	*36.2*	pc/mi/ln
LOS	*E*	

Design (N)

Design (N)

Design LOS		
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)		pc/h/ln
S		mph
D = v_p / S		pc/mi/ln
Required Number of Lanes, N		

Glossary

N - Number of lanes
V - Hourly volume
v_p - Flow rate
LOS - Level of service
S - Speed
D - Density
FFS - Free-flow speed
BFFS - Base free-flow speed
DDHV - Directional design hour volume

Factor Location

E_R - Exhibits 11-10, 11-12
E_T - Exhibits 11-10, 11-11, 11-13
f_p - Page 11-18
LOS, S, FFS, v_p - Exhibits 11-2, 11-3
f_{LW} - Exhibit 11-8
f_{LC} - Exhibit 11-9
TRD - Page 11-11

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 2:29 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*I-405 SB*
Agency or Company	*LLG*	From/To	*Palo Verde Ave/Studebaker Rd*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*PM Peak Hour*	Analysis Year	*Existing*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*10264*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length	*mi*
			Up/Down %	

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs

Lane Width		ft
Rt-Side Lat. Clearance		ft
Number of Lanes, N	*6*	
Total Ramp Density, TRD		ramps/mi
FFS (measured)	*65.0*	mph
Base free-flow Speed, BFFS		mph

Calc Speed Adj and FFS

f_{LW}		mph
f_{LC}		mph
TRD Adjustment		mph
FFS	*65.0*	mph

LOS and Performance Measures

Operational (LOS)

v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*1819*	pc/h/ln
S	*62.5*	mph
D = v_p / S	*29.1*	pc/mi/ln
LOS	*D*	

Design (N)

Design (N)

Design LOS	
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	pc/h/ln
S	mph
D = v_p / S	pc/mi/ln
Required Number of Lanes, N	

Glossary

N - Number of lanes
V - Hourly volume
v_p - Flow rate
LOS - Level of service
S - Speed
D - Density
FFS - Free-flow speed
BFFS - Base free-flow speed
DDHV - Directional design hour volume

Factor Location

E_R - Exhibits 11-10, 11-12
E_T - Exhibits 11-10, 11-11, 11-13
f_p - Page 11-18
LOS, S, FFS, v_p - Exhibits 11-2, 11-3
f_{LW} - Exhibit 11-8
f_{LC} - Exhibit 11-9
TRD - Page 11-11

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 2:29 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*I-405 SB*
Agency or Company	*LLG*	From/To	*South of Studebaker Rd*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*PM Peak Hour*	Analysis Year	*Existing*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*10033*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length	*mi*
			Up/Down %	

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs			Calc Speed Adj and FFS		
Lane Width		ft			
Rt-Side Lat. Clearance		ft	f_{LW}		mph
Number of Lanes, N	*6*		f_{LC}		mph
Total Ramp Density, TRD		ramps/mi	TRD Adjustment		mph
FFS (measured)	*65.0*	mph	FFS	*65.0*	mph
Base free-flow Speed, BFFS		mph			

LOS and Performance Measures			Design (N)	
Operational (LOS)			Design (N)	
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*1778*	pc/h/ln	Design LOS	
			v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	pc/h/ln
S	*63.0*	mph	S	mph
D = v_p / S	*28.2*	pc/mi/ln	D = v_p / S	pc/mi/ln
LOS	*D*		Required Number of Lanes, N	

Glossary		Factor Location	
N - Number of lanes	S - Speed	E_R - Exhibits 11-10, 11-12	f_{LW} - Exhibit 11-8
V - Hourly volume	D - Density	E_T - Exhibits 11-10, 11-11, 11-13	f_{LC} - Exhibit 11-9
v_p - Flow rate	FFS - Free-flow speed	f_p - Page 11-18	TRD - Page 11-11
LOS - Level of service	BFFS - Base free-flow speed	LOS, S, FFS, v_p - Exhibits 11-2, 11-3	
DDHV - Directional design hour volume			

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 2:29 PM

APPENDIX I-II

EXISTING PLUS PROJECT TRAFFIC CONDITIONS

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*SR-22 EB*
Agency or Company	*LLG*	From/To	*East of Studebaker Rd*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*AM Peak Hour*	Analysis Year	*Existing Plus Project*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*4219*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length	*mi*
			Up/Down %	

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs

Lane Width		ft
Rt-Side Lat. Clearance		ft
Number of Lanes, N	*2*	
Total Ramp Density, TRD		ramps/mi
FFS (measured)	*65.0*	mph
Base free-flow Speed, BFFS		mph

Calc Speed Adj and FFS

f_{LW}		mph
f_{LC}		mph
TRD Adjustment		mph
FFS	*65.0*	mph

LOS and Performance Measures

Operational (LOS)

v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*2243*	pc/h/ln
S	*54.9*	mph
D = v_p / S	*40.8*	pc/mi/ln
LOS	*E*	

Design (N)

Design (N)

Design LOS	
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	pc/h/ln
S	mph
D = v_p / S	pc/mi/ln
Required Number of Lanes, N	

Glossary

N - Number of lanes
V - Hourly volume
v_p - Flow rate
LOS - Level of service
S - Speed
D - Density
FFS - Free-flow speed
BFFS - Base free-flow speed
DDHV - Directional design hour volume

Factor Location

E_R - Exhibits 11-10, 11-12
E_T - Exhibits 11-10, 11-11, 11-13
f_p - Page 11-18
LOS, S, FFS, v_p - Exhibits 11-2, 11-3
f_{LW} - Exhibit 11-8
f_{LC} - Exhibit 11-9
TRD - Page 11-11

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 2:36 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*SR-22 WB*
Agency or Company	*LLG*	From/To	*East of Studebaker Rd*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*AM Peak Hour*	Analysis Year	*Existing Plus Project*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*3206*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length Up/Down %	*mi*

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs

Lane Width		ft
Rt-Side Lat. Clearance		ft
Number of Lanes, N	*2*	
Total Ramp Density, TRD		ramps/mi
FFS (measured)	*65.0*	mph
Base free-flow Speed, BFFS		mph

Calc Speed Adj and FFS

f_{LW}		mph
f_{LC}		mph
TRD Adjustment		mph
FFS	*65.0*	mph

LOS and Performance Measures

Operational (LOS)

v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*1704*	pc/h/ln
S	*63.7*	mph
D = v_p / S	*26.8*	pc/mi/ln
LOS	*D*	

Design (N)

Design (N)

Design LOS		
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)		pc/h/ln
S		mph
D = v_p / S		pc/mi/ln
Required Number of Lanes, N		

Glossary

N - Number of lanes
V - Hourly volume
v_p - Flow rate
LOS - Level of service
S - Speed
D - Density
FFS - Free-flow speed
BFFS - Base free-flow speed
DDHV - Directional design hour volume

Factor Location

E_R - Exhibits 11-10, 11-12
E_T - Exhibits 11-10, 11-11, 11-13
f_p - Page 11-18
LOS, S, FFS, v_p - Exhibits 11-2, 11-3
f_{LW} - Exhibit 11-8
f_{LC} - Exhibit 11-9
TRD - Page 11-11

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 2:37 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*I-605 NB*
Agency or Company	*LLG*	From/To	*South of Katella Ave*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*AM Peak Hour*	Analysis Year	*Existing Plus Project*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*6406*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length Up/Down %	*mi*

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs

Lane Width		ft
Rt-Side Lat. Clearance		ft
Number of Lanes, N	*6*	
Total Ramp Density, TRD		ramps/mi
FFS (measured)	*65.0*	mph
Base free-flow Speed, BFFS		mph

Calc Speed Adj and FFS

f_{LW}		mph
f_{LC}		mph
TRD Adjustment		mph
FFS	*65.0*	mph

LOS and Performance Measures

Operational (LOS)

v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*1135*	pc/h/ln
S	*65.0*	mph
D = v_p / S	*17.5*	pc/mi/ln
LOS	*B*	

Design (N)

Design (N)

Design LOS		
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)		pc/h/ln
S		mph
D = v_p / S		pc/mi/ln
Required Number of Lanes, N		

Glossary

N - Number of lanes
V - Hourly volume
v_p - Flow rate
LOS - Level of service
S - Speed
D - Density
FFS - Free-flow speed
BFFS - Base free-flow speed
DDHV - Directional design hour volume

Factor Location

E_R - Exhibits 11-10, 11-12
E_T - Exhibits 11-10, 11-11, 11-13
f_p - Page 11-18
LOS, S, FFS, v_p - Exhibits 11-2, 11-3
f_{LW} - Exhibit 11-8
f_{LC} - Exhibit 11-9
TRD - Page 11-11

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 2:37 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*I-605 SB*
Agency or Company	*LLG*	From/To	*South of Katella Ave*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*AM Peak Hour*	Analysis Year	*Existing Plus Project*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*4677*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length	*mi*
			Up/Down %	

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs			Calc Speed Adj and FFS		
Lane Width		ft			
Rt-Side Lat. Clearance		ft	f_{LW}		mph
Number of Lanes, N	*6*		f_{LC}		mph
Total Ramp Density, TRD		ramps/mi	TRD Adjustment		mph
FFS (measured)	*65.0*	mph	FFS	*65.0*	mph
Base free-flow Speed, BFFS		mph			

LOS and Performance Measures			Design (N)		
Operational (LOS)			Design (N)		
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*829*	pc/h/ln	Design LOS		
			v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)		pc/h/ln
S	*65.0*	mph	S		mph
D = v_p / S	*12.8*	pc/mi/ln	D = v_p / S		pc/mi/ln
LOS	*B*		Required Number of Lanes, N		

Glossary		Factor Location	
N - Number of lanes	S - Speed	E_R - Exhibits 11-10, 11-12	f_{LW} - Exhibit 11-8
V - Hourly volume	D - Density	E_T - Exhibits 11-10, 11-11, 11-13	f_{LC} - Exhibit 11-9
v_p - Flow rate	FFS - Free-flow speed	f_p - Page 11-18	TRD - Page 11-11
LOS - Level of service	BFFS - Base free-flow speed	LOS, S, FFS, v_p - Exhibits 11-2, 11-3	
DDHV - Directional design hour volume			

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 2:37 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*I-405 NB*
Agency or Company	*LLG*	From/To	*Bellflower Blvd/Woodruff Ave*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*AM Peak Hour*	Analysis Year	*Existing Plus Project*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*9152*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length	*mi*
			Up/Down %	

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs

Lane Width		ft
Rt-Side Lat. Clearance		ft
Number of Lanes, N	*6*	
Total Ramp Density, TRD		ramps/mi
FFS (measured)	*65.0*	mph
Base free-flow Speed, BFFS		mph

Calc Speed Adj and FFS

f_{LW}		mph
f_{LC}		mph
TRD Adjustment		mph
FFS	*65.0*	mph

LOS and Performance Measures

Operational (LOS)

v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*1622*	pc/h/ln
S	*64.3*	mph
D = v_p / S	*25.2*	pc/mi/ln
LOS	*C*	

Design (N)

Design (N)

Design LOS	
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	pc/h/ln
S	mph
D = v_p / S	pc/mi/ln
Required Number of Lanes, N	

Glossary

N - Number of lanes
V - Hourly volume
v_p - Flow rate
LOS - Level of service
S - Speed
D - Density
FFS - Free-flow speed
BFFS - Base free-flow speed
DDHV - Directional design hour volume

Factor Location

E_R - Exhibits 11-10, 11-12
E_T - Exhibits 11-10, 11-11, 11-13
f_p - Page 11-18
LOS, S, FFS, v_p - Exhibits 11-2, 11-3
f_{LW} - Exhibit 11-8
f_{LC} - Exhibit 11-9
TRD - Page 11-11

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 2:38 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*I-405 NB*
Agency or Company	*LLG*	From/To	*Woodruff Ave/Palo Verde Ave*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*AM Peak Hour*	Analysis Year	*Existing Plus Project*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*8977*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length Up/Down %	*mi*

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs

Lane Width		ft
Rt-Side Lat. Clearance		ft
Number of Lanes, N	*6*	
Total Ramp Density, TRD		ramps/mi
FFS (measured)	*65.0*	mph
Base free-flow Speed, BFFS		mph

Calc Speed Adj and FFS

f_{LW}		mph
f_{LC}		mph
TRD Adjustment		mph
FFS	*65.0*	mph

LOS and Performance Measures

Operational (LOS)

v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*1591*	pc/h/ln
S	*64.5*	mph
D = v_p / S	*24.7*	pc/mi/ln
LOS	*C*	

Design (N)

Design (N)

Design LOS		
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)		pc/h/ln
S		mph
D = v_p / S		pc/mi/ln
Required Number of Lanes, N		

Glossary

N - Number of lanes
V - Hourly volume
v_p - Flow rate
LOS - Level of service
S - Speed
D - Density
FFS - Free-flow speed
BFFS - Base free-flow speed
DDHV - Directional design hour volume

Factor Location

E_R - Exhibits 11-10, 11-12
E_T - Exhibits 11-10, 11-11, 11-13
f_p - Page 11-18
LOS, S, FFS, v_p - Exhibits 11-2, 11-3
f_{LW} - Exhibit 11-8
f_{LC} - Exhibit 11-9
TRD - Page 11-11

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 2:38 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*I-405 NB*
Agency or Company	*LLG*	From/To	*Palo Verde Ave/Studebaker Rd*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*AM Peak Hour*	Analysis Year	*Existing Plus Project*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*9326*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length Up/Down %	*mi*

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs

Lane Width		ft
Rt-Side Lat. Clearance		ft
Number of Lanes, N	*6*	
Total Ramp Density, TRD		ramps/mi
FFS (measured)	*65.0*	mph
Base free-flow Speed, BFFS		mph

Calc Speed Adj and FFS

f_{LW}		mph
f_{LC}		mph
TRD Adjustment		mph
FFS	*65.0*	mph

LOS and Performance Measures

Operational (LOS)

v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*1653*	pc/h/ln
S	*64.1*	mph
D = v_p / S	*25.8*	pc/mi/ln
LOS	*C*	

Design (N)

Design (N)

Design LOS	
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	pc/h/ln
S	mph
D = v_p / S	pc/mi/ln
Required Number of Lanes, N	

Glossary

N - Number of lanes
V - Hourly volume
v_p - Flow rate
LOS - Level of service
S - Speed
D - Density
FFS - Free-flow speed
BFFS - Base free-flow speed
DDHV - Directional design hour volume

Factor Location

E_R - Exhibits 11-10, 11-12
E_T - Exhibits 11-10, 11-11, 11-13
f_p - Page 11-18
LOS, S, FFS, v_p - Exhibits 11-2, 11-3
f_{LW} - Exhibit 11-8
f_{LC} - Exhibit 11-9
TRD - Page 11-11

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 2:39 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*I-405 NB*
Agency or Company	*LLG*	From/To	*South of Studebaker Rd*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*AM Peak Hour*	Analysis Year	*Existing Plus Project*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*9117*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length	*mi*
			Up/Down %	

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs

Lane Width		ft
Rt-Side Lat. Clearance		ft
Number of Lanes, N	*5*	
Total Ramp Density, TRD		ramps/mi
FFS (measured)	*65.0*	mph
Base free-flow Speed, BFFS		mph

Calc Speed Adj and FFS

f_{LW}		mph
f_{LC}		mph
TRD Adjustment		mph
FFS	*65.0*	mph

LOS and Performance Measures

Operational (LOS)

v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*1939*	pc/h/ln
S	*60.9*	mph
D = v_p / S	*31.8*	pc/mi/ln
LOS	*D*	

Design (N)

Design (N)

Design LOS	
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	pc/h/ln
S	mph
D = v_p / S	pc/mi/ln
Required Number of Lanes, N	

Glossary

N - Number of lanes
V - Hourly volume
v_p - Flow rate
LOS - Level of service
S - Speed
D - Density
FFS - Free-flow speed
BFFS - Base free-flow speed
DDHV - Directional design hour volume

Factor Location

E_R - Exhibits 11-10, 11-12
E_T - Exhibits 11-10, 11-11, 11-13
f_p - Page 11-18
LOS, S, FFS, v_p - Exhibits 11-2, 11-3
f_{LW} - Exhibit 11-8
f_{LC} - Exhibit 11-9
TRD - Page 11-11

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 2:39 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*I-405 SB*
Agency or Company	*LLG*	From/To	*Bellflower Blvd/Woodruff Ave*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*AM Peak Hour*	Analysis Year	*Existing Plus Project*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*8235*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length Up/Down %	*mi*

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs

Lane Width		ft
Rt-Side Lat. Clearance		ft
Number of Lanes, N	*6*	
Total Ramp Density, TRD		ramps/mi
FFS (measured)	*65.0*	mph
Base free-flow Speed, BFFS		mph

Calc Speed Adj and FFS

f_{LW}		mph
f_{LC}		mph
TRD Adjustment		mph
FFS	*65.0*	mph

LOS and Performance Measures

Operational (LOS)

v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*1459*	pc/h/ln
S	*65.0*	mph
D = v_p / S	*22.5*	pc/mi/ln
LOS	*C*	

Design (N)

Design (N)

Design LOS		
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)		pc/h/ln
S		mph
D = v_p / S		pc/mi/ln
Required Number of Lanes, N		

Glossary

N - Number of lanes
V - Hourly volume
v_p - Flow rate
LOS - Level of service
S - Speed
D - Density
FFS - Free-flow speed
BFFS - Base free-flow speed
DDHV - Directional design hour volume

Factor Location

E_R - Exhibits 11-10, 11-12
E_T - Exhibits 11-10, 11-11, 11-13
f_p - Page 11-18
LOS, S, FFS, v_p - Exhibits 11-2, 11-3
f_{LW} - Exhibit 11-8
f_{LC} - Exhibit 11-9
TRD - Page 11-11

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 2:39 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*I-405 SB*
Agency or Company	*LLG*	From/To	*Woodruff Ave/Palo Verde Ave*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*AM Peak Hour*	Analysis Year	*Existing Plus Project*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*8078*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length Up/Down %	*mi*

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs

Lane Width		ft
Rt-Side Lat. Clearance		ft
Number of Lanes, N	*5*	
Total Ramp Density, TRD		ramps/mi
FFS (measured)	*65.0*	mph
Base free-flow Speed, BFFS		mph

Calc Speed Adj and FFS

f_{LW}		mph
f_{LC}		mph
TRD Adjustment		mph
FFS	*65.0*	mph

LOS and Performance Measures

Operational (LOS)

v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*1718*	pc/h/ln
S	*63.6*	mph
D = v_p / S	*27.0*	pc/mi/ln
LOS	*D*	

Design (N)

Design (N)

Design LOS		
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)		pc/h/ln
S		mph
D = v_p / S		pc/mi/ln
Required Number of Lanes, N		

Glossary

N - Number of lanes
V - Hourly volume
v_p - Flow rate
LOS - Level of service
S - Speed
D - Density
FFS - Free-flow speed
BFFS - Base free-flow speed
DDHV - Directional design hour volume

Factor Location

E_R - Exhibits 11-10, 11-12
E_T - Exhibits 11-10, 11-11, 11-13
f_p - Page 11-18
LOS, S, FFS, v_p - Exhibits 11-2, 11-3
f_{LW} - Exhibit 11-8
f_{LC} - Exhibit 11-9
TRD - Page 11-11

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 2:40 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*I-405 SB*
Agency or Company	*LLG*	From/To	*Palo Verde Ave/Studebaker Rd*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*AM Peak Hour*	Analysis Year	*Existing Plus Project*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*8392*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length Up/Down %	*mi*

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs

Lane Width		ft
Rt-Side Lat. Clearance		ft
Number of Lanes, N	*6*	
Total Ramp Density, TRD		ramps/mi
FFS (measured)	*65.0*	mph
Base free-flow Speed, BFFS		mph

Calc Speed Adj and FFS

f_{LW}		mph
f_{LC}		mph
TRD Adjustment		mph
FFS	*65.0*	mph

LOS and Performance Measures

Operational (LOS)

v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*1487*	pc/h/ln
S	*64.9*	mph
D = v_p / S	*22.9*	pc/mi/ln
LOS	*C*	

Design (N)

Design (N)

Design LOS		
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)		pc/h/ln
S		mph
D = v_p / S		pc/mi/ln
Required Number of Lanes, N		

Glossary

N - Number of lanes	S - Speed
V - Hourly volume	D - Density
v_p - Flow rate	FFS - Free-flow speed
LOS - Level of service	BFFS - Base free-flow speed
DDHV - Directional design hour volume	

Factor Location

E_R - Exhibits 11-10, 11-12	f_{LW} - Exhibit 11-8
E_T - Exhibits 11-10, 11-11, 11-13	f_{LC} - Exhibit 11-9
f_p - Page 11-18	TRD - Page 11-11
LOS, S, FFS, v_p - Exhibits 11-2, 11-3	

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 2:40 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*I-405 SB*
Agency or Company	*LLG*	From/To	*South of Studebaker Rd*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*AM Peak Hour*	Analysis Year	*Existing Plus Project*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*8203*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length Up/Down %	*mi*

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs

Lane Width		ft
Rt-Side Lat. Clearance		ft
Number of Lanes, N	*6*	
Total Ramp Density, TRD		ramps/mi
FFS (measured)	*65.0*	mph
Base free-flow Speed, BFFS		mph

Calc Speed Adj and FFS

f_{LW}		mph
f_{LC}		mph
TRD Adjustment		mph
FFS	*65.0*	mph

LOS and Performance Measures

Operational (LOS)

v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*1454*	pc/h/ln
S	*65.0*	mph
D = v_p / S	*22.4*	pc/mi/ln
LOS	*C*	

Design (N)

Design (N)

Design LOS		
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)		pc/h/ln
S		mph
D = v_p / S		pc/mi/ln
Required Number of Lanes, N		

Glossary

N - Number of lanes
V - Hourly volume
v_p - Flow rate
LOS - Level of service
S - Speed
D - Density
FFS - Free-flow speed
BFFS - Base free-flow speed
DDHV - Directional design hour volume

Factor Location

E_R - Exhibits 11-10, 11-12
E_T - Exhibits 11-10, 11-11, 11-13
f_p - Page 11-18
LOS, S, FFS, v_p - Exhibits 11-2, 11-3
f_{LW} - Exhibit 11-8
f_{LC} - Exhibit 11-9
TRD - Page 11-11

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 2:40 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*SR-22 EB*
Agency or Company	*LLG*	From/To	*East of Studebaker Rd*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*PM Peak Hour*	Analysis Year	*Existing Plus Project*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*3971*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length	*mi*
			Up/Down %	

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs			Calc Speed Adj and FFS		
Lane Width		ft			
Rt-Side Lat. Clearance		ft	f_{LW}		mph
Number of Lanes, N	*2*		f_{LC}		mph
Total Ramp Density, TRD		ramps/mi	TRD Adjustment		mph
FFS (measured)	*65.0*	mph	FFS	*65.0*	mph
Base free-flow Speed, BFFS		mph			

LOS and Performance Measures			Design (N)		
Operational (LOS)			Design (N)		
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*2111*	pc/h/ln	Design LOS		
			v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)		pc/h/ln
S	*57.8*	mph	S		mph
D = v_p / S	*36.5*	pc/mi/ln	D = v_p / S		pc/mi/ln
LOS	*E*		Required Number of Lanes, N		

Glossary		Factor Location	
N - Number of lanes	S - Speed	E_R - Exhibits 11-10, 11-12	f_{LW} - Exhibit 11-8
V - Hourly volume	D - Density	E_T - Exhibits 11-10, 11-11, 11-13	f_{LC} - Exhibit 11-9
v_p - Flow rate	FFS - Free-flow speed	f_p - Page 11-18	TRD - Page 11-11
LOS - Level of service	BFFS - Base free-flow speed	LOS, S, FFS, v_p - Exhibits 11-2, 11-3	
DDHV - Directional design hour volume			

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 2:43 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*SR-22 WB*
Agency or Company	*LLG*	From/To	*East of Studebaker Rd*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*PM Peak Hour*	Analysis Year	*Existing Plus Project*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*4073*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length Up/Down %	*mi*

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs

Lane Width		ft
Rt-Side Lat. Clearance		ft
Number of Lanes, N	*2*	
Total Ramp Density, TRD		ramps/mi
FFS (measured)	*65.0*	mph
Base free-flow Speed, BFFS		mph

Calc Speed Adj and FFS

f_{LW}		mph
f_{LC}		mph
TRD Adjustment		mph
FFS	*65.0*	mph

LOS and Performance Measures

Operational (LOS)

v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*2165*	pc/h/ln
S	*56.7*	mph
D = v_p / S	*38.2*	pc/mi/ln
LOS	*E*	

Design (N)

Design (N)

Design LOS	
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	pc/h/ln
S	mph
D = v_p / S	pc/mi/ln
Required Number of Lanes, N	

Glossary

N - Number of lanes
V - Hourly volume
v_p - Flow rate
LOS - Level of service
S - Speed
D - Density
FFS - Free-flow speed
BFFS - Base free-flow speed
DDHV - Directional design hour volume

Factor Location

E_R - Exhibits 11-10, 11-12
E_T - Exhibits 11-10, 11-11, 11-13
f_p - Page 11-18
LOS, S, FFS, v_p - Exhibits 11-2, 11-3
f_{LW} - Exhibit 11-8
f_{LC} - Exhibit 11-9
TRD - Page 11-11

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 2:43 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*I-605 NB*
Agency or Company	*LLG*	From/To	*South of Katella Ave*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*PM Peak Hour*	Analysis Year	*Existing Plus Project*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*7644*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length	*mi*
			Up/Down %	

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs

Lane Width		ft
Rt-Side Lat. Clearance		ft
Number of Lanes, N	*6*	
Total Ramp Density, TRD		ramps/mi
FFS (measured)	*65.0*	mph
Base free-flow Speed, BFFS		mph

Calc Speed Adj and FFS

f_{LW}		mph
f_{LC}		mph
TRD Adjustment		mph
FFS	*65.0*	mph

LOS and Performance Measures

Operational (LOS)

v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*1354*	pc/h/ln
S	*65.0*	mph
D = v_p / S	*20.8*	pc/mi/ln
LOS	*C*	

Design (N)

Design (N)

Design LOS		
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)		pc/h/ln
S		mph
D = v_p / S		pc/mi/ln
Required Number of Lanes, N		

Glossary

N - Number of lanes
V - Hourly volume
v_p - Flow rate
LOS - Level of service
S - Speed
D - Density
FFS - Free-flow speed
BFFS - Base free-flow speed
DDHV - Directional design hour volume

Factor Location

E_R - Exhibits 11-10, 11-12
E_T - Exhibits 11-10, 11-11, 11-13
f_p - Page 11-18
LOS, S, FFS, v_p - Exhibits 11-2, 11-3
f_{LW} - Exhibit 11-8
f_{LC} - Exhibit 11-9
TRD - Page 11-11

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 2:44 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*I-605 SB*
Agency or Company	*LLG*	From/To	*South of Katella Ave*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*PM Peak Hour*	Analysis Year	*Existing Plus Project*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*5359*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length	*mi*
			Up/Down %	

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs

Lane Width		ft
Rt-Side Lat. Clearance		ft
Number of Lanes, N	*6*	
Total Ramp Density, TRD		ramps/mi
FFS (measured)	*65.0*	mph
Base free-flow Speed, BFFS		mph

Calc Speed Adj and FFS

f_{LW}		mph
f_{LC}		mph
TRD Adjustment		mph
FFS	*65.0*	mph

LOS and Performance Measures

Operational (LOS)

v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*950*	pc/h/ln
S	*65.0*	mph
D = v_p / S	*14.6*	pc/mi/ln
LOS	*B*	

Design (N)

Design (N)

Design LOS		
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)		pc/h/ln
S		mph
D = v_p / S		pc/mi/ln
Required Number of Lanes, N		

Glossary

N - Number of lanes
V - Hourly volume
v_p - Flow rate
LOS - Level of service
S - Speed
D - Density
FFS - Free-flow speed
BFFS - Base free-flow speed
DDHV - Directional design hour volume

Factor Location

E_R - Exhibits 11-10, 11-12
E_T - Exhibits 11-10, 11-11, 11-13
f_p - Page 11-18
LOS, S, FFS, v_p - Exhibits 11-2, 11-3
f_{LW} - Exhibit 11-8
f_{LC} - Exhibit 11-9
TRD - Page 11-11

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 2:44 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	ML	Highway/Direction of Travel	I-405 NB
Agency or Company	LLG	From/To	Bellflower Blvd/Woodruff Ave
Date Performed	1/18/17	Jurisdiction	
Analysis Time Period	PM Peak Hour	Analysis Year	Existing Plus Project

Project Description 2-16-3779 2nd & PCH Project, Long Beach

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	8059	veh/h	Peak-Hour Factor, PHF	0.95
AADT		veh/day	%Trucks and Buses, P_T	2
Peak-Hr Prop. of AADT, K			%RVs, P_R	0
Peak-Hr Direction Prop, D			General Terrain:	Level
DDHV = AADT x K x D		veh/h	Grade % Length Up/Down %	mi

Calculate Flow Adjustments

f_p	1.00	E_R	1.2
E_T	1.5	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	0.990

Speed Inputs

Lane Width		ft
Rt-Side Lat. Clearance		ft
Number of Lanes, N	6	
Total Ramp Density, TRD		ramps/mi
FFS (measured)	65.0	mph
Base free-flow Speed, BFFS		mph

Calc Speed Adj and FFS

f_{LW}		mph
f_{LC}		mph
TRD Adjustment		mph
FFS	65.0	mph

LOS and Performance Measures

Operational (LOS)

v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	1428	pc/h/ln
S	65.0	mph
D = v_p / S	22.0	pc/mi/ln
LOS	C	

Design (N)

Design (N)

Design LOS		
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)		pc/h/ln
S		mph
D = v_p / S		pc/mi/ln
Required Number of Lanes, N		

Glossary

N - Number of lanes
V - Hourly volume
v_p - Flow rate
LOS - Level of service
S - Speed
D - Density
FFS - Free-flow speed
BFFS - Base free-flow speed
DDHV - Directional design hour volume

Factor Location

E_R - Exhibits 11-10, 11-12
E_T - Exhibits 11-10, 11-11, 11-13
f_p - Page 11-18
LOS, S, FFS, v_p - Exhibits 11-2, 11-3
f_{LW} - Exhibit 11-8
f_{LC} - Exhibit 11-9
TRD - Page 11-11

Copyright © 2016 University of Florida, All Rights Reserved HCS 2010™ Version 6.80 Generated: 1/18/2017 2:44 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*I-405 NB*
Agency or Company	*LLG*	From/To	*Woodruff Ave/Palo Verde Ave*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*PM Peak Hour*	Analysis Year	*Existing Plus Project*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*7905*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length Up/Down %	*mi*

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs

Lane Width		ft
Rt-Side Lat. Clearance		ft
Number of Lanes, N	*6*	
Total Ramp Density, TRD		ramps/mi
FFS (measured)	*65.0*	mph
Base free-flow Speed, BFFS		mph

Calc Speed Adj and FFS

f_{LW}		mph
f_{LC}		mph
TRD Adjustment		mph
FFS	*65.0*	mph

LOS and Performance Measures

Operational (LOS)

v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*1401*	pc/h/ln
S	*65.0*	mph
D = v_p / S	*21.6*	pc/mi/ln
LOS	*C*	

Design (N)

Design (N)

Design LOS		
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)		pc/h/ln
S		mph
D = v_p / S		pc/mi/ln
Required Number of Lanes, N		

Glossary

N - Number of lanes
V - Hourly volume
v_p - Flow rate
LOS - Level of service
S - Speed
D - Density
FFS - Free-flow speed
BFFS - Base free-flow speed
DDHV - Directional design hour volume

Factor Location

E_R - Exhibits 11-10, 11-12
E_T - Exhibits 11-10, 11-11, 11-13
f_p - Page 11-18
LOS, S, FFS, v_p - Exhibits 11-2, 11-3
f_{LW} - Exhibit 11-8
f_{LC} - Exhibit 11-9
TRD - Page 11-11

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 2:45 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*I-405 NB*
Agency or Company	*LLG*	From/To	*Palo Verde Ave/Studebaker Rd*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*PM Peak Hour*	Analysis Year	*Existing Plus Project*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*8212*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length Up/Down %	*mi*

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs

Lane Width		ft
Rt-Side Lat. Clearance		ft
Number of Lanes, N	*6*	
Total Ramp Density, TRD		ramps/mi
FFS (measured)	*65.0*	mph
Base free-flow Speed, BFFS		mph

Calc Speed Adj and FFS

f_{LW}		mph
f_{LC}		mph
TRD Adjustment		mph
FFS	*65.0*	mph

LOS and Performance Measures

Operational (LOS)

v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*1455*	pc/h/ln
S	*65.0*	mph
D = v_p / S	*22.4*	pc/mi/ln
LOS	*C*	

Design (N)

Design (N)

Design LOS		
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)		pc/h/ln
S		mph
D = v_p / S		pc/mi/ln
Required Number of Lanes, N		

Glossary

N - Number of lanes
V - Hourly volume
v_p - Flow rate
LOS - Level of service
S - Speed
D - Density
FFS - Free-flow speed
BFFS - Base free-flow speed
DDHV - Directional design hour volume

Factor Location

E_R - Exhibits 11-10, 11-12
E_T - Exhibits 11-10, 11-11, 11-13
f_p - Page 11-18
LOS, S, FFS, v_p - Exhibits 11-2, 11-3
f_{LW} - Exhibit 11-8
f_{LC} - Exhibit 11-9
TRD - Page 11-11

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 2:45 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*I-405 NB*
Agency or Company	*LLG*	From/To	*South of Studebaker Rd*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*PM Peak Hour*	Analysis Year	*Existing Plus Project*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*8027*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length	*mi*
			Up/Down %	

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs			Calc Speed Adj and FFS		
Lane Width		ft			
Rt-Side Lat. Clearance		ft	f_{LW}		mph
Number of Lanes, N	*5*		f_{LC}		mph
Total Ramp Density, TRD		ramps/mi	TRD Adjustment		mph
FFS (measured)	*65.0*	mph	FFS	*65.0*	mph
Base free-flow Speed, BFFS		mph			

LOS and Performance Measures			Design (N)	
Operational (LOS)			Design (N)	
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*1707*	pc/h/ln	Design LOS	
			v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	pc/h/ln
S	*63.7*	mph	S	mph
D = v_p / S	*26.8*	pc/mi/ln	D = v_p / S	pc/mi/ln
LOS	*D*		Required Number of Lanes, N	

Glossary		Factor Location	
N - Number of lanes	S - Speed	E_R - Exhibits 11-10, 11-12	f_{LW} - Exhibit 11-8
V - Hourly volume	D - Density	E_T - Exhibits 11-10, 11-11, 11-13	f_{LC} - Exhibit 11-9
v_p - Flow rate	FFS - Free-flow speed	f_p - Page 11-18	TRD - Page 11-11
LOS - Level of service	BFFS - Base free-flow speed	LOS, S, FFS, v_p - Exhibits 11-2, 11-3	
DDHV - Directional design hour volume			

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 2:45 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*I-405 SB*
Agency or Company	*LLG*	From/To	*Bellflower Blvd/Woodruff Ave*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*PM Peak Hour*	Analysis Year	*Existing Plus Project*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*10076*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length Up/Down %	*mi*

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs

Lane Width		ft
Rt-Side Lat. Clearance		ft
Number of Lanes, N	*6*	
Total Ramp Density, TRD		ramps/mi
FFS (measured)	*65.0*	mph
Base free-flow Speed, BFFS		mph

Calc Speed Adj and FFS

f_{LW}		mph
f_{LC}		mph
TRD Adjustment		mph
FFS	*65.0*	mph

LOS and Performance Measures

Operational (LOS)

v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*1785*	pc/h/ln
S	*62.9*	mph
D = v_p / S	*28.4*	pc/mi/ln
LOS	*D*	

Design (N)

Design (N)

Design LOS		
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)		pc/h/ln
S		mph
D = v_p / S		pc/mi/ln
Required Number of Lanes, N		

Glossary

N - Number of lanes	S - Speed
V - Hourly volume	D - Density
v_p - Flow rate	FFS - Free-flow speed
LOS - Level of service	BFFS - Base free-flow speed
DDHV - Directional design hour volume	

Factor Location

E_R - Exhibits 11-10, 11-12	f_{LW} - Exhibit 11-8
E_T - Exhibits 11-10, 11-11, 11-13	f_{LC} - Exhibit 11-9
f_p - Page 11-18	TRD - Page 11-11
LOS, S, FFS, v_p - Exhibits 11-2, 11-3	

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 2:46 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*I-405 SB*
Agency or Company	*LLG*	From/To	*Woodruff Ave/Palo Verde Ave*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*PM Peak Hour*	Analysis Year	*Existing Plus Project*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*9884*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length Up/Down %	*mi*

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs

Lane Width		ft
Rt-Side Lat. Clearance		ft
Number of Lanes, N	*5*	
Total Ramp Density, TRD		ramps/mi
FFS (measured)	*65.0*	mph
Base free-flow Speed, BFFS		mph

Calc Speed Adj and FFS

f_{LW}		mph
f_{LC}		mph
TRD Adjustment		mph
FFS	*65.0*	mph

LOS and Performance Measures

Operational (LOS)

v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*2102*	pc/h/ln
S	*58.0*	mph
D = v_p / S	*36.2*	pc/mi/ln
LOS	*E*	

Design (N)

Design (N)

Design LOS	
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	pc/h/ln
S	mph
D = v_p / S	pc/mi/ln
Required Number of Lanes, N	

Glossary

N - Number of lanes
V - Hourly volume
v_p - Flow rate
LOS - Level of service
S - Speed
D - Density
FFS - Free-flow speed
BFFS - Base free-flow speed
DDHV - Directional design hour volume

Factor Location

E_R - Exhibits 11-10, 11-12
E_T - Exhibits 11-10, 11-11, 11-13
f_p - Page 11-18
LOS, S, FFS, v_p - Exhibits 11-2, 11-3
f_{LW} - Exhibit 11-8
f_{LC} - Exhibit 11-9
TRD - Page 11-11

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 2:46 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*I-405 SB*
Agency or Company	*LLG*	From/To	*Palo Verde Ave/Studebaker Rd*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*PM Peak Hour*	Analysis Year	*Existing Plus Project*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*10269*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length Up/Down %	*mi*

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs

Lane Width		ft
Rt-Side Lat. Clearance		ft
Number of Lanes, N	*6*	
Total Ramp Density, TRD		ramps/mi
FFS (measured)	*65.0*	mph
Base free-flow Speed, BFFS		mph

Calc Speed Adj and FFS

f_{LW}		mph
f_{LC}		mph
TRD Adjustment		mph
FFS	*65.0*	mph

LOS and Performance Measures

Operational (LOS)

v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*1820*	pc/h/ln
S	*62.5*	mph
D = v_p / S	*29.1*	pc/mi/ln
LOS	*D*	

Design (N)

Design (N)

Design LOS		
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)		pc/h/ln
S		mph
D = v_p / S		pc/mi/ln
Required Number of Lanes, N		

Glossary

N - Number of lanes
V - Hourly volume
v_p - Flow rate
LOS - Level of service
S - Speed
D - Density
FFS - Free-flow speed
BFFS - Base free-flow speed
DDHV - Directional design hour volume

Factor Location

E_R - Exhibits 11-10, 11-12
E_T - Exhibits 11-10, 11-11, 11-13
f_p - Page 11-18
LOS, S, FFS, v_p - Exhibits 11-2, 11-3
f_{LW} - Exhibit 11-8
f_{LC} - Exhibit 11-9
TRD - Page 11-11

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 2:46 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*I-405 SB*
Agency or Company	*LLG*	From/To	*South of Studebaker Rd*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*PM Peak Hour*	Analysis Year	*Existing Plus Project*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*10038*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length	*mi*
			Up/Down %	

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs			Calc Speed Adj and FFS		
Lane Width		ft			
Rt-Side Lat. Clearance		ft	f_{LW}		mph
Number of Lanes, N	*6*		f_{LC}		mph
Total Ramp Density, TRD		ramps/mi	TRD Adjustment		mph
FFS (measured)	*65.0*	mph	FFS	*65.0*	mph
Base free-flow Speed, BFFS		mph			

LOS and Performance Measures			Design (N)	
Operational (LOS)			Design (N)	
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*1779*	pc/h/ln	Design LOS	
			v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	pc/h/ln
S	*63.0*	mph	S	mph
D = v_p / S	*28.3*	pc/mi/ln	D = v_p / S	pc/mi/ln
LOS	*D*		Required Number of Lanes, N	

Glossary		Factor Location	
N - Number of lanes	S - Speed	E_R - Exhibits 11-10, 11-12	f_{LW} - Exhibit 11-8
V - Hourly volume	D - Density	E_T - Exhibits 11-10, 11-11, 11-13	f_{LC} - Exhibit 11-9
v_p - Flow rate	FFS - Free-flow speed	f_p - Page 11-18	TRD - Page 11-11
LOS - Level of service	BFFS - Base free-flow speed	LOS, S, FFS, v_p - Exhibits 11-2, 11-3	
DDHV - Directional design hour volume			

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 2:47 PM

APPENDIX I-III

YEAR 2019 CUMULATIVE TRAFFIC CONDITIONS

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*SR-22 EB*
Agency or Company	*LLG*	From/To	*East of Studebaker Rd*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*AM Peak Hour*	Analysis Year	*Year 2019*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*4370*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length Up/Down %	*mi*

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs

Lane Width		ft
Rt-Side Lat. Clearance		ft
Number of Lanes, N	*2*	
Total Ramp Density, TRD		ramps/mi
FFS (measured)	*65.0*	mph
Base free-flow Speed, BFFS		mph

Calc Speed Adj and FFS

f_{LW}		mph
f_{LC}		mph
TRD Adjustment		mph
FFS	*65.0*	mph

LOS and Performance Measures

Operational (LOS)

v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*2323*	pc/h/ln
S	*52.9*	mph
D = v_p / S	*43.9*	pc/mi/ln
LOS	*E*	

Design (N)

Design (N)

Design LOS		
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)		pc/h/ln
S		mph
D = v_p / S		pc/mi/ln
Required Number of Lanes, N		

Glossary

N - Number of lanes
V - Hourly volume
v_p - Flow rate
LOS - Level of service
S - Speed
D - Density
FFS - Free-flow speed
BFFS - Base free-flow speed
DDHV - Directional design hour volume

Factor Location

E_R - Exhibits 11-10, 11-12
E_T - Exhibits 11-10, 11-11, 11-13
f_p - Page 11-18
LOS, S, FFS, v_p - Exhibits 11-2, 11-3
f_{LW} - Exhibit 11-8
f_{LC} - Exhibit 11-9
TRD - Page 11-11

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 3:02 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*SR-22 WB*
Agency or Company	*LLG*	From/To	*East of Studebaker Rd*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*AM Peak Hour*	Analysis Year	*Year 2019*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*3354*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length Up/Down %	*mi*

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs

Lane Width		ft
Rt-Side Lat. Clearance		ft
Number of Lanes, N	*2*	
Total Ramp Density, TRD		ramps/mi
FFS (measured)	*65.0*	mph
Base free-flow Speed, BFFS		mph

Calc Speed Adj and FFS

f_{LW}		mph
f_{LC}		mph
TRD Adjustment		mph
FFS	*65.0*	mph

LOS and Performance Measures

Operational (LOS)

v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*1783*	pc/h/ln
S	*62.9*	mph
D = v_p / S	*28.3*	pc/mi/ln
LOS	*D*	

Design (N)

Design (N)

Design LOS		
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)		pc/h/ln
S		mph
D = v_p / S		pc/mi/ln
Required Number of Lanes, N		

Glossary

N - Number of lanes
V - Hourly volume
v_p - Flow rate
LOS - Level of service
S - Speed
D - Density
FFS - Free-flow speed
BFFS - Base free-flow speed
DDHV - Directional design hour volume

Factor Location

E_R - Exhibits 11-10, 11-12
E_T - Exhibits 11-10, 11-11, 11-13
f_p - Page 11-18
LOS, S, FFS, v_p - Exhibits 11-2, 11-3
f_{LW} - Exhibit 11-8
f_{LC} - Exhibit 11-9
TRD - Page 11-11

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 3:02 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*I-605 NB*
Agency or Company	*LLG*	From/To	*South of Katella Ave*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*AM Peak Hour*	Analysis Year	*Year 2019*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*6593*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length Up/Down %	*mi*

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs

Lane Width		ft
Rt-Side Lat. Clearance		ft
Number of Lanes, N	*6*	
Total Ramp Density, TRD		ramps/mi
FFS (measured)	*65.0*	mph
Base free-flow Speed, BFFS		mph

Calc Speed Adj and FFS

f_{LW}		mph
f_{LC}		mph
TRD Adjustment		mph
FFS	*65.0*	mph

LOS and Performance Measures

Operational (LOS)

v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*1168*	pc/h/ln
S	*65.0*	mph
D = v_p / S	*18.0*	pc/mi/ln
LOS	*B*	

Design (N)

Design (N)

Design LOS		
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)		pc/h/ln
S		mph
D = v_p / S		pc/mi/ln
Required Number of Lanes, N		

Glossary

N - Number of lanes
V - Hourly volume
v_p - Flow rate
LOS - Level of service
S - Speed
D - Density
FFS - Free-flow speed
BFFS - Base free-flow speed
DDHV - Directional design hour volume

Factor Location

E_R - Exhibits 11-10, 11-12
E_T - Exhibits 11-10, 11-11, 11-13
f_p - Page 11-18
LOS, S, FFS, v_p - Exhibits 11-2, 11-3
f_{LW} - Exhibit 11-8
f_{LC} - Exhibit 11-9
TRD - Page 11-11

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 3:02 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*I-605 SB*
Agency or Company	*LLG*	From/To	*South of Katella Ave*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*AM Peak Hour*	Analysis Year	*Year 2019*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*4810*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length	*mi*
			Up/Down %	

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs

Lane Width		ft
Rt-Side Lat. Clearance		ft
Number of Lanes, N	*6*	
Total Ramp Density, TRD		ramps/mi
FFS (measured)	*65.0*	mph
Base free-flow Speed, BFFS		mph

Calc Speed Adj and FFS

f_{LW}		mph
f_{LC}		mph
TRD Adjustment		mph
FFS	*65.0*	mph

LOS and Performance Measures

Operational (LOS)

v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*852*	pc/h/ln
S	*65.0*	mph
D = v_p / S	*13.1*	pc/mi/ln
LOS	*B*	

Design (N)

Design (N)

Design LOS	
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	pc/h/ln
S	mph
D = v_p / S	pc/mi/ln
Required Number of Lanes, N	

Glossary

N - Number of lanes
V - Hourly volume
v_p - Flow rate
LOS - Level of service
S - Speed
D - Density
FFS - Free-flow speed
BFFS - Base free-flow speed
DDHV - Directional design hour volume

Factor Location

E_R - Exhibits 11-10, 11-12
E_T - Exhibits 11-10, 11-11, 11-13
f_p - Page 11-18
LOS, S, FFS, v_p - Exhibits 11-2, 11-3
f_{LW} - Exhibit 11-8
f_{LC} - Exhibit 11-9
TRD - Page 11-11

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 3:03 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*I-405 NB*
Agency or Company	*LLG*	From/To	*Bellflower Blvd/Woodruff Ave*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*AM Peak Hour*	Analysis Year	*Year 2019*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*9434*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length	*mi*
			Up/Down %	

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs

Lane Width		ft
Rt-Side Lat. Clearance		ft
Number of Lanes, N	*6*	
Total Ramp Density, TRD		ramps/mi
FFS (measured)	*65.0*	mph
Base free-flow Speed, BFFS		mph

Calc Speed Adj and FFS

f_{LW}		mph
f_{LC}		mph
TRD Adjustment		mph
FFS	*65.0*	mph

LOS and Performance Measures

Operational (LOS)

v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*1672*	pc/h/ln
S	*64.0*	mph
D = v_p / S	*26.1*	pc/mi/ln
LOS	*D*	

Design (N)

Design (N)

Design LOS		
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)		pc/h/ln
S		mph
D = v_p / S		pc/mi/ln
Required Number of Lanes, N		

Glossary

N - Number of lanes	S - Speed
V - Hourly volume	D - Density
v_p - Flow rate	FFS - Free-flow speed
LOS - Level of service	BFFS - Base free-flow speed
DDHV - Directional design hour volume	

Factor Location

E_R - Exhibits 11-10, 11-12	f_{LW} - Exhibit 11-8
E_T - Exhibits 11-10, 11-11, 11-13	f_{LC} - Exhibit 11-9
f_p - Page 11-18	TRD - Page 11-11
LOS, S, FFS, v_p - Exhibits 11-2, 11-3	

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 3:03 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*I-405 NB*
Agency or Company	*LLG*	From/To	*Woodruff Ave/Palo Verde Ave*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*AM Peak Hour*	Analysis Year	*Year 2019*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*9253*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length Up/Down %	*mi*

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs			Calc Speed Adj and FFS		
Lane Width		ft			
Rt-Side Lat. Clearance		ft	f_{LW}		mph
Number of Lanes, N	*6*		f_{LC}		mph
Total Ramp Density, TRD		ramps/mi	TRD Adjustment		mph
FFS (measured)	*65.0*	mph	FFS	*65.0*	mph
Base free-flow Speed, BFFS		mph			

LOS and Performance Measures			Design (N)	
Operational (LOS)			Design (N)	
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*1640*	pc/h/ln	Design LOS	
			v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	pc/h/ln
S	*64.2*	mph	S	mph
D = v_p / S	*25.6*	pc/mi/ln	D = v_p / S	pc/mi/ln
LOS	*C*		Required Number of Lanes, N	

Glossary		Factor Location	
N - Number of lanes	S - Speed	E_R - Exhibits 11-10, 11-12	f_{LW} - Exhibit 11-8
V - Hourly volume	D - Density	E_T - Exhibits 11-10, 11-11, 11-13	f_{LC} - Exhibit 11-9
v_p - Flow rate	FFS - Free-flow speed	f_p - Page 11-18	TRD - Page 11-11
LOS - Level of service	BFFS - Base free-flow speed	LOS, S, FFS, v_p - Exhibits 11-2, 11-3	
DDHV - Directional design hour volume			

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 3:04 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*I-405 NB*
Agency or Company	*LLG*	From/To	*Palo Verde Ave/Studebaker Rd*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*AM Peak Hour*	Analysis Year	*Year 2019*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*9613*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length Up/Down %	*mi*

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs

Lane Width		ft
Rt-Side Lat. Clearance		ft
Number of Lanes, N	*6*	
Total Ramp Density, TRD		ramps/mi
FFS (measured)	*65.0*	mph
Base free-flow Speed, BFFS		mph

Calc Speed Adj and FFS

f_{LW}		mph
f_{LC}		mph
TRD Adjustment		mph
FFS	*65.0*	mph

LOS and Performance Measures

Operational (LOS)

v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*1703*	pc/h/ln
S	*63.7*	mph
D = v_p / S	*26.7*	pc/mi/ln
LOS	*D*	

Design (N)

Design (N)

Design LOS	
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	pc/h/ln
S	mph
D = v_p / S	pc/mi/ln
Required Number of Lanes, N	

Glossary

N - Number of lanes
V - Hourly volume
v_p - Flow rate
LOS - Level of service
S - Speed
D - Density
FFS - Free-flow speed
BFFS - Base free-flow speed
DDHV - Directional design hour volume

Factor Location

E_R - Exhibits 11-10, 11-12
E_T - Exhibits 11-10, 11-11, 11-13
f_p - Page 11-18
LOS, S, FFS, v_p - Exhibits 11-2, 11-3
f_{LW} - Exhibit 11-8
f_{LC} - Exhibit 11-9
TRD - Page 11-11

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 3:04 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*I-405 NB*
Agency or Company	*LLG*	From/To	*South of Studebaker Rd*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*AM Peak Hour*	Analysis Year	*Year 2019*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*9398*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length Up/Down %	*mi*

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs

Lane Width		ft
Rt-Side Lat. Clearance		ft
Number of Lanes, N	*5*	
Total Ramp Density, TRD		ramps/mi
FFS (measured)	*65.0*	mph
Base free-flow Speed, BFFS		mph

Calc Speed Adj and FFS

f_{LW}		mph
f_{LC}		mph
TRD Adjustment		mph
FFS	*65.0*	mph

LOS and Performance Measures

Operational (LOS)

v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*1998*	pc/h/ln
S	*59.9*	mph
D = v_p / S	*33.3*	pc/mi/ln
LOS	*D*	

Design (N)

Design (N)

Design LOS	
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	pc/h/ln
S	mph
D = v_p / S	pc/mi/ln
Required Number of Lanes, N	

Glossary

N - Number of lanes
V - Hourly volume
v_p - Flow rate
LOS - Level of service
S - Speed
D - Density
FFS - Free-flow speed
BFFS - Base free-flow speed
DDHV - Directional design hour volume

Factor Location

E_R - Exhibits 11-10, 11-12
E_T - Exhibits 11-10, 11-11, 11-13
f_p - Page 11-18
LOS, S, FFS, v_p - Exhibits 11-2, 11-3
f_{LW} - Exhibit 11-8
f_{LC} - Exhibit 11-9
TRD - Page 11-11

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 3:04 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*I-405 SB*
Agency or Company	*LLG*	From/To	*Bellflower Blvd/Woodruff Ave*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*AM Peak Hour*	Analysis Year	*Year 2019*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*8484*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length Up/Down %	*mi*

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs

Lane Width		ft
Rt-Side Lat. Clearance		ft
Number of Lanes, N	*6*	
Total Ramp Density, TRD		ramps/mi
FFS (measured)	*65.0*	mph
Base free-flow Speed, BFFS		mph

Calc Speed Adj and FFS

f_{LW}		mph
f_{LC}		mph
TRD Adjustment		mph
FFS	*65.0*	mph

LOS and Performance Measures

Operational (LOS)

v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*1503*	pc/h/ln
S	*64.8*	mph
D = v_p / S	*23.2*	pc/mi/ln
LOS	*C*	

Design (N)

Design (N)

Design LOS		
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)		pc/h/ln
S		mph
D = v_p / S		pc/mi/ln
Required Number of Lanes, N		

Glossary

N - Number of lanes
V - Hourly volume
v_p - Flow rate
LOS - Level of service
S - Speed
D - Density
FFS - Free-flow speed
BFFS - Base free-flow speed
DDHV - Directional design hour volume

Factor Location

E_R - Exhibits 11-10, 11-12
E_T - Exhibits 11-10, 11-11, 11-13
f_p - Page 11-18
LOS, S, FFS, v_p - Exhibits 11-2, 11-3
f_{LW} - Exhibit 11-8
f_{LC} - Exhibit 11-9
TRD - Page 11-11

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 3:05 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*I-405 SB*
Agency or Company	*LLG*	From/To	*Woodruff Ave/Palo Verde Ave*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*AM Peak Hour*	Analysis Year	*Year 2019*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*8322*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length Up/Down %	*mi*

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs

Lane Width		ft
Rt-Side Lat. Clearance		ft
Number of Lanes, N	*5*	
Total Ramp Density, TRD		ramps/mi
FFS (measured)	*65.0*	mph
Base free-flow Speed, BFFS		mph

Calc Speed Adj and FFS

f_{LW}		mph
f_{LC}		mph
TRD Adjustment		mph
FFS	*65.0*	mph

LOS and Performance Measures

Operational (LOS)

v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*1770*	pc/h/ln
S	*63.1*	mph
D = v_p / S	*28.1*	pc/mi/ln
LOS	*D*	

Design (N)

Design (N)

Design LOS		
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)		pc/h/ln
S		mph
D = v_p / S		pc/mi/ln
Required Number of Lanes, N		

Glossary

N - Number of lanes	S - Speed
V - Hourly volume	D - Density
v_p - Flow rate	FFS - Free-flow speed
LOS - Level of service	BFFS - Base free-flow speed
DDHV - Directional design hour volume	

Factor Location

E_R - Exhibits 11-10, 11-12	f_{LW} - Exhibit 11-8
E_T - Exhibits 11-10, 11-11, 11-13	f_{LC} - Exhibit 11-9
f_p - Page 11-18	TRD - Page 11-11
LOS, S, FFS, v_p - Exhibits 11-2, 11-3	

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 3:05 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*I-405 SB*
Agency or Company	*LLG*	From/To	*Palo Verde Ave/Studebaker Rd*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*AM Peak Hour*	Analysis Year	*Year 2019*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*8646*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length Up/Down %	*mi*

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs

Lane Width		ft
Rt-Side Lat. Clearance		ft
Number of Lanes, N	*6*	
Total Ramp Density, TRD		ramps/mi
FFS (measured)	*65.0*	mph
Base free-flow Speed, BFFS		mph

Calc Speed Adj and FFS

f_{LW}		mph
f_{LC}		mph
TRD Adjustment		mph
FFS	*65.0*	mph

LOS and Performance Measures

Operational (LOS)

v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*1532*	pc/h/ln
S	*64.8*	mph
D = v_p / S	*23.7*	pc/mi/ln
LOS	*C*	

Design (N)

Design (N)

Design LOS		
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)		pc/h/ln
S		mph
D = v_p / S		pc/mi/ln
Required Number of Lanes, N		

Glossary

N - Number of lanes	S - Speed
V - Hourly volume	D - Density
v_p - Flow rate	FFS - Free-flow speed
LOS - Level of service	BFFS - Base free-flow speed
DDHV - Directional design hour volume	

Factor Location

E_R - Exhibits 11-10, 11-12	f_{LW} - Exhibit 11-8
E_T - Exhibits 11-10, 11-11, 11-13	f_{LC} - Exhibit 11-9
f_p - Page 11-18	TRD - Page 11-11
LOS, S, FFS, v_p - Exhibits 11-2, 11-3	

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 3:06 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*I-405 SB*
Agency or Company	*LLG*	From/To	*South of Studebaker Rd*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*AM Peak Hour*	Analysis Year	*Year 2019*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*8451*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length	*mi*
			Up/Down %	

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs			Calc Speed Adj and FFS		
Lane Width		ft			
Rt-Side Lat. Clearance		ft	f_{LW}		mph
Number of Lanes, N	*6*		f_{LC}		mph
Total Ramp Density, TRD		ramps/mi	TRD Adjustment		mph
FFS (measured)	*65.0*	mph	FFS	*65.0*	mph
Base free-flow Speed, BFFS		mph			

LOS and Performance Measures			Design (N)	
Operational (LOS)			Design (N)	
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*1497*	pc/h/ln	Design LOS	
			v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	pc/h/ln
S	*64.9*	mph	S	mph
D = v_p / S	*23.1*	pc/mi/ln	D = v_p / S	pc/mi/ln
LOS	*C*		Required Number of Lanes, N	

Glossary		Factor Location	
N - Number of lanes	S - Speed	E_R - Exhibits 11-10, 11-12	f_{LW} - Exhibit 11-8
V - Hourly volume	D - Density	E_T - Exhibits 11-10, 11-11, 11-13	f_{LC} - Exhibit 11-9
v_p - Flow rate	FFS - Free-flow speed	f_p - Page 11-18	TRD - Page 11-11
LOS - Level of service	BFFS - Base free-flow speed	LOS, S, FFS, v_p - Exhibits 11-2, 11-3	
DDHV - Directional design hour volume			

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 3:06 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*SR-22 EB*
Agency or Company	*LLG*	From/To	*East of Studebaker Rd*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*PM Peak Hour*	Analysis Year	*Year 2019*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*4128*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length	*mi*
			Up/Down %	

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs			Calc Speed Adj and FFS		
Lane Width		ft			
Rt-Side Lat. Clearance		ft	f_{LW}		mph
Number of Lanes, N	*2*		f_{LC}		mph
Total Ramp Density, TRD		ramps/mi	TRD Adjustment		mph
FFS (measured)	*65.0*	mph	FFS	*65.0*	mph
Base free-flow Speed, BFFS		mph			

LOS and Performance Measures			Design (N)	
Operational (LOS)			Design (N)	
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*2194*	pc/h/ln	Design LOS	
			v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	pc/h/ln
S	*56.1*	mph	S	mph
D = v_p / S	*39.1*	pc/mi/ln	D = v_p / S	pc/mi/ln
LOS	*E*		Required Number of Lanes, N	

Glossary		Factor Location	
N - Number of lanes	S - Speed	E_R - Exhibits 11-10, 11-12	f_{LW} - Exhibit 11-8
V - Hourly volume	D - Density	E_T - Exhibits 11-10, 11-11, 11-13	f_{LC} - Exhibit 11-9
v_p - Flow rate	FFS - Free-flow speed	f_p - Page 11-18	TRD - Page 11-11
LOS - Level of service	BFFS - Base free-flow speed	LOS, S, FFS, v_p - Exhibits 11-2, 11-3	
DDHV - Directional design hour volume			

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 3:16 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*SR-22 WB*
Agency or Company	*LLG*	From/To	*East of Studebaker Rd*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*PM Peak Hour*	Analysis Year	*Year 2019*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*4202*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length Up/Down %	*mi*

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs

Lane Width		ft
Rt-Side Lat. Clearance		ft
Number of Lanes, N	*2*	
Total Ramp Density, TRD		ramps/mi
FFS (measured)	*65.0*	mph
Base free-flow Speed, BFFS		mph

Calc Speed Adj and FFS

f_{LW}		mph
f_{LC}		mph
TRD Adjustment		mph
FFS	*65.0*	mph

LOS and Performance Measures

Operational (LOS)

v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*2234*	pc/h/ln
S	*55.1*	mph
D = v_p / S	*40.5*	pc/mi/ln
LOS	*E*	

Design (N)

Design (N)

Design LOS		
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)		pc/h/ln
S		mph
D = v_p / S		pc/mi/ln
Required Number of Lanes, N		

Glossary

N - Number of lanes
V - Hourly volume
v_p - Flow rate
LOS - Level of service
S - Speed
D - Density
FFS - Free-flow speed
BFFS - Base free-flow speed
DDHV - Directional design hour volume

Factor Location

E_R - Exhibits 11-10, 11-12
E_T - Exhibits 11-10, 11-11, 11-13
f_p - Page 11-18
LOS, S, FFS, v_p - Exhibits 11-2, 11-3
f_{LW} - Exhibit 11-8
f_{LC} - Exhibit 11-9
TRD - Page 11-11

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 3:16 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*I-605 NB*
Agency or Company	*LLG*	From/To	*South of Katella Ave*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*PM Peak Hour*	Analysis Year	*Year 2019*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*7861*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length Up/Down %	*mi*

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs

Lane Width		ft
Rt-Side Lat. Clearance		ft
Number of Lanes, N	*6*	
Total Ramp Density, TRD		ramps/mi
FFS (measured)	*65.0*	mph
Base free-flow Speed, BFFS		mph

Calc Speed Adj and FFS

f_{LW}		mph
f_{LC}		mph
TRD Adjustment		mph
FFS	*65.0*	mph

LOS and Performance Measures

Operational (LOS)

v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*1393*	pc/h/ln
S	*65.0*	mph
D = v_p / S	*21.4*	pc/mi/ln
LOS	*C*	

Design (N)

Design (N)

Design LOS		
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)		pc/h/ln
S		mph
D = v_p / S		pc/mi/ln
Required Number of Lanes, N		

Glossary

N - Number of lanes
V - Hourly volume
v_p - Flow rate
LOS - Level of service
S - Speed
D - Density
FFS - Free-flow speed
BFFS - Base free-flow speed
DDHV - Directional design hour volume

Factor Location

E_R - Exhibits 11-10, 11-12
E_T - Exhibits 11-10, 11-11, 11-13
f_p - Page 11-18
LOS, S, FFS, v_p - Exhibits 11-2, 11-3
f_{LW} - Exhibit 11-8
f_{LC} - Exhibit 11-9
TRD - Page 11-11

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 3:16 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*I-605 SB*
Agency or Company	*LLG*	From/To	*South of Katella Ave*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*PM Peak Hour*	Analysis Year	*Year 2019*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*5505*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length	*mi*
			Up/Down %	

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs

Lane Width		ft
Rt-Side Lat. Clearance		ft
Number of Lanes, N	*6*	
Total Ramp Density, TRD		ramps/mi
FFS (measured)	*65.0*	mph
Base free-flow Speed, BFFS		mph

Calc Speed Adj and FFS

f_{LW}		mph
f_{LC}		mph
TRD Adjustment		mph
FFS	*65.0*	mph

LOS and Performance Measures

Operational (LOS)

v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*975*	pc/h/ln
S	*65.0*	mph
D = v_p / S	*15.0*	pc/mi/ln
LOS	*B*	

Design (N)

Design (N)

Design LOS		
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)		pc/h/ln
S		mph
D = v_p / S		pc/mi/ln
Required Number of Lanes, N		

Glossary

N - Number of lanes
V - Hourly volume
v_p - Flow rate
LOS - Level of service
S - Speed
D - Density
FFS - Free-flow speed
BFFS - Base free-flow speed
DDHV - Directional design hour volume

Factor Location

E_R - Exhibits 11-10, 11-12
E_T - Exhibits 11-10, 11-11, 11-13
f_p - Page 11-18
LOS, S, FFS, v_p - Exhibits 11-2, 11-3
f_{LW} - Exhibit 11-8
f_{LC} - Exhibit 11-9
TRD - Page 11-11

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 3:17 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*I-405 NB*
Agency or Company	*LLG*	From/To	*Bellflower Blvd/Woodruff Ave*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*PM Peak Hour*	Analysis Year	*Year 2019*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*8302*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length Up/Down %	*mi*

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs			Calc Speed Adj and FFS		
Lane Width		ft			
Rt-Side Lat. Clearance		ft	f_{LW}		mph
Number of Lanes, N	*6*		f_{LC}		mph
Total Ramp Density, TRD		ramps/mi	TRD Adjustment		mph
FFS (measured)	*65.0*	mph	FFS	*65.0*	mph
Base free-flow Speed, BFFS		mph			

LOS and Performance Measures			Design (N)	
Operational (LOS)			Design (N)	
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*1471*	pc/h/ln	Design LOS	
			v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	pc/h/ln
S	*64.9*	mph	S	mph
D = v_p / S	*22.7*	pc/mi/ln	D = v_p / S	pc/mi/ln
LOS	*C*		Required Number of Lanes, N	

Glossary		Factor Location	
N - Number of lanes	S - Speed	E_R - Exhibits 11-10, 11-12	f_{LW} - Exhibit 11-8
V - Hourly volume	D - Density	E_T - Exhibits 11-10, 11-11, 11-13	f_{LC} - Exhibit 11-9
v_p - Flow rate	FFS - Free-flow speed	f_p - Page 11-18	TRD - Page 11-11
LOS - Level of service	BFFS - Base free-flow speed	LOS, S, FFS, v_p - Exhibits 11-2, 11-3	
DDHV - Directional design hour volume			

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 3:17 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*I-405 NB*
Agency or Company	*LLG*	From/To	*Woodruff Ave/Palo Verde Ave*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*PM Peak Hour*	Analysis Year	*Year 2019*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*8143*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length	*mi*
			Up/Down %	

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs

Lane Width		ft
Rt-Side Lat. Clearance		ft
Number of Lanes, N	*6*	
Total Ramp Density, TRD		ramps/mi
FFS (measured)	*65.0*	mph
Base free-flow Speed, BFFS		mph

Calc Speed Adj and FFS

f_{LW}		mph
f_{LC}		mph
TRD Adjustment		mph
FFS	*65.0*	mph

LOS and Performance Measures

Operational (LOS)

v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*1443*	pc/h/ln
S	*65.0*	mph
D = v_p / S	*22.2*	pc/mi/ln
LOS	*C*	

Design (N)

Design (N)

Design LOS		
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)		pc/h/ln
S		mph
D = v_p / S		pc/mi/ln
Required Number of Lanes, N		

Glossary

N - Number of lanes
V - Hourly volume
v_p - Flow rate
LOS - Level of service
S - Speed
D - Density
FFS - Free-flow speed
BFFS - Base free-flow speed
DDHV - Directional design hour volume

Factor Location

E_R - Exhibits 11-10, 11-12
E_T - Exhibits 11-10, 11-11, 11-13
f_p - Page 11-18
LOS, S, FFS, v_p - Exhibits 11-2, 11-3
f_{LW} - Exhibit 11-8
f_{LC} - Exhibit 11-9
TRD - Page 11-11

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 3:17 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*I-405 NB*
Agency or Company	*LLG*	From/To	*Palo Verde Ave/Studebaker Rd*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*PM Peak Hour*	Analysis Year	*Year 2019*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*8459*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length Up/Down %	*mi*

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs

Lane Width		ft
Rt-Side Lat. Clearance		ft
Number of Lanes, N	*6*	
Total Ramp Density, TRD		ramps/mi
FFS (measured)	*65.0*	mph
Base free-flow Speed, BFFS		mph

Calc Speed Adj and FFS

f_{LW}		mph
f_{LC}		mph
TRD Adjustment		mph
FFS	*65.0*	mph

LOS and Performance Measures

Operational (LOS)

v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*1499*	pc/h/ln
S	*64.9*	mph
D = v_p / S	*23.1*	pc/mi/ln
LOS	*C*	

Design (N)

Design (N)

Design LOS	
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	pc/h/ln
S	mph
D = v_p / S	pc/mi/ln
Required Number of Lanes, N	

Glossary

N - Number of lanes
V - Hourly volume
v_p - Flow rate
LOS - Level of service
S - Speed
D - Density
FFS - Free-flow speed
BFFS - Base free-flow speed
DDHV - Directional design hour volume

Factor Location

E_R - Exhibits 11-10, 11-12
E_T - Exhibits 11-10, 11-11, 11-13
f_p - Page 11-18
LOS, S, FFS, v_p - Exhibits 11-2, 11-3
f_{LW} - Exhibit 11-8
f_{LC} - Exhibit 11-9
TRD - Page 11-11

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 3:18 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*I-405 NB*
Agency or Company	*LLG*	From/To	*South of Studebaker Rd*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*PM Peak Hour*	Analysis Year	*Year 2019*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*8269*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length Up/Down %	*mi*

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs

Lane Width		ft
Rt-Side Lat. Clearance		ft
Number of Lanes, N	*5*	
Total Ramp Density, TRD		ramps/mi
FFS (measured)	*65.0*	mph
Base free-flow Speed, BFFS		mph

Calc Speed Adj and FFS

f_{LW}		mph
f_{LC}		mph
TRD Adjustment		mph
FFS	*65.0*	mph

LOS and Performance Measures

Operational (LOS)

v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*1758*	pc/h/ln
S	*63.2*	mph
D = v_p / S	*27.8*	pc/mi/ln
LOS	*D*	

Design (N)

Design (N)

Design LOS		
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)		pc/h/ln
S		mph
D = v_p / S		pc/mi/ln
Required Number of Lanes, N		

Glossary

N - Number of lanes
V - Hourly volume
v_p - Flow rate
LOS - Level of service
S - Speed
D - Density
FFS - Free-flow speed
BFFS - Base free-flow speed
DDHV - Directional design hour volume

Factor Location

E_R - Exhibits 11-10, 11-12
E_T - Exhibits 11-10, 11-11, 11-13
f_p - Page 11-18
LOS, S, FFS, v_p - Exhibits 11-2, 11-3
f_{LW} - Exhibit 11-8
f_{LC} - Exhibit 11-9
TRD - Page 11-11

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 3:18 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*I-405 SB*
Agency or Company	*LLG*	From/To	*Bellflower Blvd/Woodruff Ave*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*PM Peak Hour*	Analysis Year	*Year 2019*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*10380*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length	*mi*
			Up/Down %	

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs			Calc Speed Adj and FFS		
Lane Width		ft			
Rt-Side Lat. Clearance		ft	f_{LW}		mph
Number of Lanes, N	*6*		f_{LC}		mph
Total Ramp Density, TRD		ramps/mi	TRD Adjustment		mph
FFS (measured)	*65.0*	mph	FFS	*65.0*	mph
Base free-flow Speed, BFFS		mph			

LOS and Performance Measures			Design (N)	
Operational (LOS)			Design (N)	
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*1839*	pc/h/ln	Design LOS	
			v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	pc/h/ln
S	*62.3*	mph	S	mph
D = v_p / S	*29.5*	pc/mi/ln	D = v_p / S	pc/mi/ln
LOS	*D*		Required Number of Lanes, N	

Glossary		Factor Location	
N - Number of lanes	S - Speed	E_R - Exhibits 11-10, 11-12	f_{LW} - Exhibit 11-8
V - Hourly volume	D - Density	E_T - Exhibits 11-10, 11-11, 11-13	f_{LC} - Exhibit 11-9
v_p - Flow rate	FFS - Free-flow speed	f_p - Page 11-18	TRD - Page 11-11
LOS - Level of service	BFFS - Base free-flow speed	LOS, S, FFS, v_p - Exhibits 11-2, 11-3	
DDHV - Directional design hour volume			

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 3:18 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*I-405 SB*
Agency or Company	*LLG*	From/To	*Woodruff Ave/Palo Verde Ave*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*PM Peak Hour*	Analysis Year	*Year 2019*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*10182*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length Up/Down %	*mi*

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs			Calc Speed Adj and FFS		
Lane Width		ft			
Rt-Side Lat. Clearance		ft	f_{LW}		mph
Number of Lanes, N	*5*		f_{LC}		mph
Total Ramp Density, TRD		ramps/mi	TRD Adjustment		mph
FFS (measured)	*65.0*	mph	FFS	*65.0*	mph
Base free-flow Speed, BFFS		mph			

LOS and Performance Measures			Design (N)	
Operational (LOS)			Design (N)	
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*2165*	pc/h/ln	Design LOS	
			v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	pc/h/ln
S	*56.7*	mph	S	mph
D = v_p / S	*38.2*	pc/mi/ln	D = v_p / S	pc/mi/ln
LOS	*E*		Required Number of Lanes, N	

Glossary		Factor Location	
N - Number of lanes	S - Speed	E_R - Exhibits 11-10, 11-12	f_{LW} - Exhibit 11-8
V - Hourly volume	D - Density	E_T - Exhibits 11-10, 11-11, 11-13	f_{LC} - Exhibit 11-9
v_p - Flow rate	FFS - Free-flow speed	f_p - Page 11-18	TRD - Page 11-11
LOS - Level of service	BFFS - Base free-flow speed	LOS, S, FFS, v_p - Exhibits 11-2, 11-3	
DDHV - Directional design hour volume			

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 3:19 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*I-405 SB*
Agency or Company	*LLG*	From/To	*Palo Verde Ave/Studebaker Rd*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*PM Peak Hour*	Analysis Year	*Year 2019*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*10579*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length Up/Down %	*mi*

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs

Lane Width		ft
Rt-Side Lat. Clearance		ft
Number of Lanes, N	*6*	
Total Ramp Density, TRD		ramps/mi
FFS (measured)	*65.0*	mph
Base free-flow Speed, BFFS		mph

Calc Speed Adj and FFS

f_{LW}		mph
f_{LC}		mph
TRD Adjustment		mph
FFS	*65.0*	mph

LOS and Performance Measures

Operational (LOS)

v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*1875*	pc/h/ln
S	*61.8*	mph
D = v_p / S	*30.3*	pc/mi/ln
LOS	*D*	

Design (N)

Design (N)

Design LOS		
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)		pc/h/ln
S		mph
D = v_p / S		pc/mi/ln
Required Number of Lanes, N		

Glossary

N - Number of lanes
V - Hourly volume
v_p - Flow rate
LOS - Level of service
S - Speed
D - Density
FFS - Free-flow speed
BFFS - Base free-flow speed
DDHV - Directional design hour volume

Factor Location

E_R - Exhibits 11-10, 11-12
E_T - Exhibits 11-10, 11-11, 11-13
f_p - Page 11-18
LOS, S, FFS, v_p - Exhibits 11-2, 11-3
f_{LW} - Exhibit 11-8
f_{LC} - Exhibit 11-9
TRD - Page 11-11

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 3:19 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*I-405 SB*
Agency or Company	*LLG*	From/To	*South of Studebaker Rd*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*PM Peak Hour*	Analysis Year	*Year 2019*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*10341*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length	*mi*
			Up/Down %	

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs			Calc Speed Adj and FFS		
Lane Width		ft			
Rt-Side Lat. Clearance		ft	f_{LW}		mph
Number of Lanes, N	*6*		f_{LC}		mph
Total Ramp Density, TRD		ramps/mi	TRD Adjustment		mph
FFS (measured)	*65.0*	mph	FFS	*65.0*	mph
Base free-flow Speed, BFFS		mph			

LOS and Performance Measures			Design (N)	
Operational (LOS)			Design (N)	
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*1832*	pc/h/ln	Design LOS	
			v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	pc/h/ln
S	*62.4*	mph	S	mph
D = v_p / S	*29.4*	pc/mi/ln	D = v_p / S	pc/mi/ln
LOS	*D*		Required Number of Lanes, N	

Glossary		Factor Location	
N - Number of lanes	S - Speed	E_R - Exhibits 11-10, 11-12	f_{LW} - Exhibit 11-8
V - Hourly volume	D - Density	E_T - Exhibits 11-10, 11-11, 11-13	f_{LC} - Exhibit 11-9
v_p - Flow rate	FFS - Free-flow speed	f_p - Page 11-18	TRD - Page 11-11
LOS - Level of service	BFFS - Base free-flow speed	LOS, S, FFS, v_p - Exhibits 11-2, 11-3	
DDHV - Directional design hour volume			

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 3:19 PM

APPENDIX I-IV

YEAR 2019 CUMULATIVE PLUS PROJECT TRAFFIC CONDITIONS

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*SR-22 EB*
Agency or Company	*LLG*	From/To	*East of Studebaker Rd*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*AM Peak Hour*	Analysis Year	*Year 2019 Plus Project*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*4380*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length Up/Down %	*mi*

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs

Lane Width		ft
Rt-Side Lat. Clearance		ft
Number of Lanes, N	*2*	
Total Ramp Density, TRD		ramps/mi
FFS (measured)	*65.0*	mph
Base free-flow Speed, BFFS		mph

Calc Speed Adj and FFS

f_{LW}		mph
f_{LC}		mph
TRD Adjustment		mph
FFS	*65.0*	mph

LOS and Performance Measures

Operational (LOS)

v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*2328*	pc/h/ln
S	*52.8*	mph
D = v_p / S	*44.1*	pc/mi/ln
LOS	*E*	

Design (N)

Design (N)

Design LOS	
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	pc/h/ln
S	mph
D = v_p / S	pc/mi/ln
Required Number of Lanes, N	

Glossary

N - Number of lanes
V - Hourly volume
v_p - Flow rate
LOS - Level of service
S - Speed
D - Density
FFS - Free-flow speed
BFFS - Base free-flow speed
DDHV - Directional design hour volume

Factor Location

E_R - Exhibits 11-10, 11-12
E_T - Exhibits 11-10, 11-11, 11-13
f_p - Page 11-18
LOS, S, FFS, v_p - Exhibits 11-2, 11-3
f_{LW} - Exhibit 11-8
f_{LC} - Exhibit 11-9
TRD - Page 11-11

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 3:25 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*SR-22 WB*
Agency or Company	*LLG*	From/To	*East of Studebaker Rd*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*AM Peak Hour*	Analysis Year	*Year 2019 Plus Project*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*3367*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length Up/Down %	*mi*

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs

Lane Width		ft
Rt-Side Lat. Clearance		ft
Number of Lanes, N	*2*	
Total Ramp Density, TRD		ramps/mi
FFS (measured)	*65.0*	mph
Base free-flow Speed, BFFS		mph

Calc Speed Adj and FFS

f_{LW}		mph
f_{LC}		mph
TRD Adjustment		mph
FFS	*65.0*	mph

LOS and Performance Measures

Operational (LOS)

v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*1790*	pc/h/ln
S	*62.8*	mph
D = v_p / S	*28.5*	pc/mi/ln
LOS	*D*	

Design (N)

Design (N)

Design LOS		
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)		pc/h/ln
S		mph
D = v_p / S		pc/mi/ln
Required Number of Lanes, N		

Glossary

N - Number of lanes
V - Hourly volume
v_p - Flow rate
LOS - Level of service
S - Speed
D - Density
FFS - Free-flow speed
BFFS - Base free-flow speed
DDHV - Directional design hour volume

Factor Location

E_R - Exhibits 11-10, 11-12
E_T - Exhibits 11-10, 11-11, 11-13
f_p - Page 11-18
LOS, S, FFS, v_p - Exhibits 11-2, 11-3
f_{LW} - Exhibit 11-8
f_{LC} - Exhibit 11-9
TRD - Page 11-11

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 3:26 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*I-605 NB*
Agency or Company	*LLG*	From/To	*South of Katella Ave*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*AM Peak Hour*	Analysis Year	*Year 2019 Plus Project*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*6598*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length Up/Down %	*mi*

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs

Lane Width		ft
Rt-Side Lat. Clearance		ft
Number of Lanes, N	*6*	
Total Ramp Density, TRD		ramps/mi
FFS (measured)	*65.0*	mph
Base free-flow Speed, BFFS		mph

Calc Speed Adj and FFS

f_{LW}		mph
f_{LC}		mph
TRD Adjustment		mph
FFS	*65.0*	mph

LOS and Performance Measures

Operational (LOS)

v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*1169*	pc/h/ln
S	*65.0*	mph
D = v_p / S	*18.0*	pc/mi/ln
LOS	*B*	

Design (N)

Design (N)

Design LOS		
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)		pc/h/ln
S		mph
D = v_p / S		pc/mi/ln
Required Number of Lanes, N		

Glossary

N - Number of lanes
V - Hourly volume
v_p - Flow rate
LOS - Level of service
S - Speed
D - Density
FFS - Free-flow speed
BFFS - Base free-flow speed
DDHV - Directional design hour volume

Factor Location

E_R - Exhibits 11-10, 11-12
E_T - Exhibits 11-10, 11-11, 11-13
f_p - Page 11-18
LOS, S, FFS, v_p - Exhibits 11-2, 11-3
f_{LW} - Exhibit 11-8
f_{LC} - Exhibit 11-9
TRD - Page 11-11

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 3:26 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*I-605 SB*
Agency or Company	*LLG*	From/To	*South of Katella Ave*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*AM Peak Hour*	Analysis Year	*Year 2019 Plus Project*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*4817*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length	*mi*
			Up/Down %	

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs			Calc Speed Adj and FFS		
Lane Width		ft			
Rt-Side Lat. Clearance		ft	f_{LW}		mph
Number of Lanes, N	*6*		f_{LC}		mph
Total Ramp Density, TRD		ramps/mi	TRD Adjustment		mph
FFS (measured)	*65.0*	mph	FFS	*65.0*	mph
Base free-flow Speed, BFFS		mph			

LOS and Performance Measures			Design (N)	
Operational (LOS)			Design (N)	
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*854*	pc/h/ln	Design LOS	
			v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	pc/h/ln
S	*65.0*	mph	S	mph
D = v_p / S	*13.1*	pc/mi/ln	D = v_p / S	pc/mi/ln
LOS	*B*		Required Number of Lanes, N	

Glossary		Factor Location	
N - Number of lanes	S - Speed	E_R - Exhibits 11-10, 11-12	f_{LW} - Exhibit 11-8
V - Hourly volume	D - Density	E_T - Exhibits 11-10, 11-11, 11-13	f_{LC} - Exhibit 11-9
v_p - Flow rate	FFS - Free-flow speed	f_p - Page 11-18	TRD - Page 11-11
LOS - Level of service	BFFS - Base free-flow speed	LOS, S, FFS, v_p - Exhibits 11-2, 11-3	
DDHV - Directional design hour volume			

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 3:26 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*I-405 NB*
Agency or Company	*LLG*	From/To	*Bellflower Blvd/Woodruff Ave*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*AM Peak Hour*	Analysis Year	*Year 2019 Plus Project*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*9434*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length	*mi*
			Up/Down %	

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs

Lane Width		ft
Rt-Side Lat. Clearance		ft
Number of Lanes, N	*6*	
Total Ramp Density, TRD		ramps/mi
FFS (measured)	*65.0*	mph
Base free-flow Speed, BFFS		mph

Calc Speed Adj and FFS

f_{LW}		mph
f_{LC}		mph
TRD Adjustment		mph
FFS	*65.0*	mph

LOS and Performance Measures

Operational (LOS)

v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*1672*	pc/h/ln
S	*64.0*	mph
D = v_p / S	*26.1*	pc/mi/ln
LOS	*D*	

Design (N)

Design (N)

Design LOS		
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)		pc/h/ln
S		mph
D = v_p / S		pc/mi/ln
Required Number of Lanes, N		

Glossary

N - Number of lanes
V - Hourly volume
v_p - Flow rate
LOS - Level of service
S - Speed
D - Density
FFS - Free-flow speed
BFFS - Base free-flow speed
DDHV - Directional design hour volume

Factor Location

E_R - Exhibits 11-10, 11-12
E_T - Exhibits 11-10, 11-11, 11-13
f_p - Page 11-18
LOS, S, FFS, v_p - Exhibits 11-2, 11-3
f_{LW} - Exhibit 11-8
f_{LC} - Exhibit 11-9
TRD - Page 11-11

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 3:27 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*I-405 NB*
Agency or Company	*LLG*	From/To	*Woodruff Ave/Palo Verde Ave*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*AM Peak Hour*	Analysis Year	*Year 2019 Plus Project*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*9253*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length Up/Down %	*mi*

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs

Lane Width		ft
Rt-Side Lat. Clearance		ft
Number of Lanes, N	*6*	
Total Ramp Density, TRD		ramps/mi
FFS (measured)	*65.0*	mph
Base free-flow Speed, BFFS		mph

Calc Speed Adj and FFS

f_{LW}		mph
f_{LC}		mph
TRD Adjustment		mph
FFS	*65.0*	mph

LOS and Performance Measures

Operational (LOS)

v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*1640*	pc/h/ln
S	*64.2*	mph
D = v_p / S	*25.6*	pc/mi/ln
LOS	*C*	

Design (N)

Design (N)

Design LOS		
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)		pc/h/ln
S		mph
D = v_p / S		pc/mi/ln
Required Number of Lanes, N		

Glossary

N - Number of lanes
V - Hourly volume
v_p - Flow rate
LOS - Level of service
S - Speed
D - Density
FFS - Free-flow speed
BFFS - Base free-flow speed
DDHV - Directional design hour volume

Factor Location

E_R - Exhibits 11-10, 11-12
E_T - Exhibits 11-10, 11-11, 11-13
f_p - Page 11-18
LOS, S, FFS, v_p - Exhibits 11-2, 11-3
f_{LW} - Exhibit 11-8
f_{LC} - Exhibit 11-9
TRD - Page 11-11

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 3:27 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*I-405 NB*
Agency or Company	*LLG*	From/To	*Palo Verde Ave/Studebaker Rd*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*AM Peak Hour*	Analysis Year	*Year 2019 Plus Project*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*9613*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length Up/Down %	*mi*

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs

Lane Width		ft
Rt-Side Lat. Clearance		ft
Number of Lanes, N	*6*	
Total Ramp Density, TRD		ramps/mi
FFS (measured)	*65.0*	mph
Base free-flow Speed, BFFS		mph

Calc Speed Adj and FFS

f_{LW}		mph
f_{LC}		mph
TRD Adjustment		mph
FFS	*65.0*	mph

LOS and Performance Measures

Operational (LOS)

v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*1703*	pc/h/ln
S	*63.7*	mph
D = v_p / S	*26.7*	pc/mi/ln
LOS	*D*	

Design (N)

Design (N)

Design LOS	
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	pc/h/ln
S	mph
D = v_p / S	pc/mi/ln
Required Number of Lanes, N	

Glossary

N - Number of lanes
V - Hourly volume
v_p - Flow rate
LOS - Level of service
S - Speed
D - Density
FFS - Free-flow speed
BFFS - Base free-flow speed
DDHV - Directional design hour volume

Factor Location

E_R - Exhibits 11-10, 11-12
E_T - Exhibits 11-10, 11-11, 11-13
f_p - Page 11-18
LOS, S, FFS, v_p - Exhibits 11-2, 11-3
f_{LW} - Exhibit 11-8
f_{LC} - Exhibit 11-9
TRD - Page 11-11

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 3:27 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*I-405 NB*
Agency or Company	*LLG*	From/To	*South of Studebaker Rd*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*AM Peak Hour*	Analysis Year	*Year 2019 Plus Project*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*9398*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length	*mi*
			Up/Down %	

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs

Lane Width		ft
Rt-Side Lat. Clearance		ft
Number of Lanes, N	*5*	
Total Ramp Density, TRD		ramps/mi
FFS (measured)	*65.0*	mph
Base free-flow Speed, BFFS		mph

Calc Speed Adj and FFS

f_{LW}		mph
f_{LC}		mph
TRD Adjustment		mph
FFS	*65.0*	mph

LOS and Performance Measures

Operational (LOS)

v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*1998*	pc/h/ln
S	*59.9*	mph
D = v_p / S	*33.3*	pc/mi/ln
LOS	*D*	

Design (N)

Design (N)

Design LOS		
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)		pc/h/ln
S		mph
D = v_p / S		pc/mi/ln
Required Number of Lanes, N		

Glossary

N - Number of lanes
V - Hourly volume
v_p - Flow rate
LOS - Level of service
S - Speed
D - Density
FFS - Free-flow speed
BFFS - Base free-flow speed
DDHV - Directional design hour volume

Factor Location

E_R - Exhibits 11-10, 11-12
E_T - Exhibits 11-10, 11-11, 11-13
f_p - Page 11-18
LOS, S, FFS, v_p - Exhibits 11-2, 11-3
f_{LW} - Exhibit 11-8
f_{LC} - Exhibit 11-9
TRD - Page 11-11

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 3:28 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*I-405 SB*
Agency or Company	*LLG*	From/To	*Bellflower Blvd/Woodruff Ave*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*AM Peak Hour*	Analysis Year	*Year 2019 Plus Project*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*8485*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length Up/Down %	*mi*

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs

Lane Width		ft
Rt-Side Lat. Clearance		ft
Number of Lanes, N	*6*	
Total Ramp Density, TRD		ramps/mi
FFS (measured)	*65.0*	mph
Base free-flow Speed, BFFS		mph

Calc Speed Adj and FFS

f_{LW}		mph
f_{LC}		mph
TRD Adjustment		mph
FFS	*65.0*	mph

LOS and Performance Measures

Operational (LOS)

v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*1503*	pc/h/ln
S	*64.8*	mph
D = v_p / S	*23.2*	pc/mi/ln
LOS	*C*	

Design (N)

Design (N)

Design LOS	
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	pc/h/ln
S	mph
D = v_p / S	pc/mi/ln
Required Number of Lanes, N	

Glossary

N - Number of lanes
V - Hourly volume
v_p - Flow rate
LOS - Level of service
S - Speed
D - Density
FFS - Free-flow speed
BFFS - Base free-flow speed
DDHV - Directional design hour volume

Factor Location

E_R - Exhibits 11-10, 11-12
E_T - Exhibits 11-10, 11-11, 11-13
f_p - Page 11-18
LOS, S, FFS, v_p - Exhibits 11-2, 11-3
f_{LW} - Exhibit 11-8
f_{LC} - Exhibit 11-9
TRD - Page 11-11

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 3:28 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*I-405 SB*
Agency or Company	*LLG*	From/To	*Woodruff Ave/Palo Verde Ave*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*AM Peak Hour*	Analysis Year	*Year 2019 Plus Project*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*8323*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length	*mi*
			Up/Down %	

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs

Lane Width		ft
Rt-Side Lat. Clearance		ft
Number of Lanes, N	*5*	
Total Ramp Density, TRD		ramps/mi
FFS (measured)	*65.0*	mph
Base free-flow Speed, BFFS		mph

Calc Speed Adj and FFS

f_{LW}		mph
f_{LC}		mph
TRD Adjustment		mph
FFS	*65.0*	mph

LOS and Performance Measures

Operational (LOS)

v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*1770*	pc/h/ln
S	*63.1*	mph
D = v_p / S	*28.1*	pc/mi/ln
LOS	*D*	

Design (N)

Design (N)

Design LOS		
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)		pc/h/ln
S		mph
D = v_p / S		pc/mi/ln
Required Number of Lanes, N		

Glossary

N - Number of lanes
V - Hourly volume
v_p - Flow rate
LOS - Level of service
S - Speed
D - Density
FFS - Free-flow speed
BFFS - Base free-flow speed
DDHV - Directional design hour volume

Factor Location

E_R - Exhibits 11-10, 11-12
E_T - Exhibits 11-10, 11-11, 11-13
f_p - Page 11-18
LOS, S, FFS, v_p - Exhibits 11-2, 11-3
f_{LW} - Exhibit 11-8
f_{LC} - Exhibit 11-9
TRD - Page 11-11

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 3:28 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*I-405 SB*
Agency or Company	*LLG*	From/To	*Palo Verde Ave/Studebaker Rd*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*AM Peak Hour*	Analysis Year	*Year 2019 Plus Project*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*8647*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length Up/Down %	*mi*

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs

Lane Width		ft
Rt-Side Lat. Clearance		ft
Number of Lanes, N	*6*	
Total Ramp Density, TRD		ramps/mi
FFS (measured)	*65.0*	mph
Base free-flow Speed, BFFS		mph

Calc Speed Adj and FFS

f_{LW}		mph
f_{LC}		mph
TRD Adjustment		mph
FFS	*65.0*	mph

LOS and Performance Measures

Operational (LOS)

v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*1532*	pc/h/ln
S	*64.8*	mph
D = v_p / S	*23.7*	pc/mi/ln
LOS	*C*	

Design (N)

Design (N)

Design LOS		
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)		pc/h/ln
S		mph
D = v_p / S		pc/mi/ln
Required Number of Lanes, N		

Glossary

N - Number of lanes
V - Hourly volume
v_p - Flow rate
LOS - Level of service
S - Speed
D - Density
FFS - Free-flow speed
BFFS - Base free-flow speed
DDHV - Directional design hour volume

Factor Location

E_R - Exhibits 11-10, 11-12
E_T - Exhibits 11-10, 11-11, 11-13
f_p - Page 11-18
LOS, S, FFS, v_p - Exhibits 11-2, 11-3
f_{LW} - Exhibit 11-8
f_{LC} - Exhibit 11-9
TRD - Page 11-11

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 3:29 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*I-405 SB*
Agency or Company	*LLG*	From/To	*South of Studebaker Rd*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*AM Peak Hour*	Analysis Year	*Year 2019 Plus Project*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*8452*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length	*mi*
			Up/Down %	

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs			Calc Speed Adj and FFS		
Lane Width		ft			
Rt-Side Lat. Clearance		ft	f_{LW}		mph
Number of Lanes, N	*6*		f_{LC}		mph
Total Ramp Density, TRD		ramps/mi	TRD Adjustment		mph
FFS (measured)	*65.0*	mph	FFS	*65.0*	mph
Base free-flow Speed, BFFS		mph			

LOS and Performance Measures			Design (N)		
Operational (LOS)			Design (N)		
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*1498*	pc/h/ln	Design LOS		
			v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)		pc/h/ln
S	*64.9*	mph	S		mph
D = v_p / S	*23.1*	pc/mi/ln	D = v_p / S		pc/mi/ln
LOS	*C*		Required Number of Lanes, N		

Glossary		Factor Location	
N - Number of lanes	S - Speed	E_R - Exhibits 11-10, 11-12	f_{LW} - Exhibit 11-8
V - Hourly volume	D - Density	E_T - Exhibits 11-10, 11-11, 11-13	f_{LC} - Exhibit 11-9
v_p - Flow rate	FFS - Free-flow speed	f_p - Page 11-18	TRD - Page 11-11
LOS - Level of service	BFFS - Base free-flow speed	LOS, S, FFS, v_p - Exhibits 11-2, 11-3	
DDHV - Directional design hour volume			

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 3:29 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*SR-22 EB*
Agency or Company	*LLG*	From/To	*East of Studebaker Rd*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*PM Peak Hour*	Analysis Year	*Year 2019 Plus Project*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*4155*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length Up/Down %	*mi*

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs

Lane Width		ft
Rt-Side Lat. Clearance		ft
Number of Lanes, N	*2*	
Total Ramp Density, TRD		ramps/mi
FFS (measured)	*65.0*	mph
Base free-flow Speed, BFFS		mph

Calc Speed Adj and FFS

f_{LW}		mph
f_{LC}		mph
TRD Adjustment		mph
FFS	*65.0*	mph

LOS and Performance Measures

Operational (LOS)

v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*2209*	pc/h/ln
S	*55.7*	mph
D = v_p / S	*39.6*	pc/mi/ln
LOS	*E*	

Design (N)

Design (N)

Design LOS	
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	pc/h/ln
S	mph
D = v_p / S	pc/mi/ln
Required Number of Lanes, N	

Glossary

N - Number of lanes
V - Hourly volume
v_p - Flow rate
LOS - Level of service
S - Speed
D - Density
FFS - Free-flow speed
BFFS - Base free-flow speed
DDHV - Directional design hour volume

Factor Location

E_R - Exhibits 11-10, 11-12
E_T - Exhibits 11-10, 11-11, 11-13
f_p - Page 11-18
LOS, S, FFS, v_p - Exhibits 11-2, 11-3
f_{LW} - Exhibit 11-8
f_{LC} - Exhibit 11-9
TRD - Page 11-11

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 4:10 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*SR-22 WB*
Agency or Company	*LLG*	From/To	*East of Studebaker Rd*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*PM Peak Hour*	Analysis Year	*Year 2019 Plus Project*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*4234*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length Up/Down %	*mi*

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs

Lane Width		ft
Rt-Side Lat. Clearance		ft
Number of Lanes, N	*2*	
Total Ramp Density, TRD		ramps/mi
FFS (measured)	*65.0*	mph
Base free-flow Speed, BFFS		mph

Calc Speed Adj and FFS

f_{LW}		mph
f_{LC}		mph
TRD Adjustment		mph
FFS	*65.0*	mph

LOS and Performance Measures

Operational (LOS)

v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*2251*	pc/h/ln
S	*54.7*	mph
D = v_p / S	*41.1*	pc/mi/ln
LOS	*E*	

Design (N)

Design (N)

Design LOS	
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	pc/h/ln
S	mph
D = v_p / S	pc/mi/ln
Required Number of Lanes, N	

Glossary

N - Number of lanes
V - Hourly volume
v_p - Flow rate
LOS - Level of service
S - Speed
D - Density
FFS - Free-flow speed
BFFS - Base free-flow speed
DDHV - Directional design hour volume

Factor Location

E_R - Exhibits 11-10, 11-12
E_T - Exhibits 11-10, 11-11, 11-13
f_p - Page 11-18
LOS, S, FFS, v_p - Exhibits 11-2, 11-3
f_{LW} - Exhibit 11-8
f_{LC} - Exhibit 11-9
TRD - Page 11-11

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 4:10 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*I-605 NB*
Agency or Company	*LLG*	From/To	*South of Katella Ave*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*PM Peak Hour*	Analysis Year	*Year 2019 Plus Project*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*7873*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length Up/Down %	*mi*

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs

Lane Width		ft
Rt-Side Lat. Clearance		ft
Number of Lanes, N	*6*	
Total Ramp Density, TRD		ramps/mi
FFS (measured)	*65.0*	mph
Base free-flow Speed, BFFS		mph

Calc Speed Adj and FFS

f_{LW}		mph
f_{LC}		mph
TRD Adjustment		mph
FFS	*65.0*	mph

LOS and Performance Measures

Operational (LOS)

v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*1395*	pc/h/ln
S	*65.0*	mph
D = v_p / S	*21.5*	pc/mi/ln
LOS	*C*	

Design (N)

Design (N)

Design LOS		
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)		pc/h/ln
S		mph
D = v_p / S		pc/mi/ln
Required Number of Lanes, N		

Glossary

N - Number of lanes
V - Hourly volume
v_p - Flow rate
LOS - Level of service
S - Speed
D - Density
FFS - Free-flow speed
BFFS - Base free-flow speed
DDHV - Directional design hour volume

Factor Location

E_R - Exhibits 11-10, 11-12
E_T - Exhibits 11-10, 11-11, 11-13
f_p - Page 11-18
LOS, S, FFS, v_p - Exhibits 11-2, 11-3
f_{LW} - Exhibit 11-8
f_{LC} - Exhibit 11-9
TRD - Page 11-11

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 4:10 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*I-605 SB*
Agency or Company	*LLG*	From/To	*South of Katella Ave*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*PM Peak Hour*	Analysis Year	*Year 2019 Plus Project*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*5519*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length	*mi*
			Up/Down %	

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs

Lane Width		ft
Rt-Side Lat. Clearance		ft
Number of Lanes, N	*6*	
Total Ramp Density, TRD		ramps/mi
FFS (measured)	*65.0*	mph
Base free-flow Speed, BFFS		mph

Calc Speed Adj and FFS

f_{LW}		mph
f_{LC}		mph
TRD Adjustment		mph
FFS	*65.0*	mph

LOS and Performance Measures

Operational (LOS)

v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*978*	pc/h/ln
S	*65.0*	mph
D = v_p / S	*15.0*	pc/mi/ln
LOS	*B*	

Design (N)

Design (N)

Design LOS		
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)		pc/h/ln
S		mph
D = v_p / S		pc/mi/ln
Required Number of Lanes, N		

Glossary

N - Number of lanes
V - Hourly volume
v_p - Flow rate
LOS - Level of service
S - Speed
D - Density
FFS - Free-flow speed
BFFS - Base free-flow speed
DDHV - Directional design hour volume

Factor Location

E_R - Exhibits 11-10, 11-12
E_T - Exhibits 11-10, 11-11, 11-13
f_p - Page 11-18
LOS, S, FFS, v_p - Exhibits 11-2, 11-3
f_{LW} - Exhibit 11-8
f_{LC} - Exhibit 11-9
TRD - Page 11-11

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 4:10 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*I-405 NB*
Agency or Company	*LLG*	From/To	*Bellflower Blvd/Woodruff Ave*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*PM Peak Hour*	Analysis Year	*Year 2019 Plus Project*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*8305*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length Up/Down %	*mi*

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs

Lane Width		ft
Rt-Side Lat. Clearance		ft
Number of Lanes, N	*6*	
Total Ramp Density, TRD		ramps/mi
FFS (measured)	*65.0*	mph
Base free-flow Speed, BFFS		mph

Calc Speed Adj and FFS

f_{LW}		mph
f_{LC}		mph
TRD Adjustment		mph
FFS	*65.0*	mph

LOS and Performance Measures

Operational (LOS)

v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*1472*	pc/h/ln
S	*64.9*	mph
D = v_p / S	*22.7*	pc/mi/ln
LOS	*C*	

Design (N)

Design (N)

Design LOS		
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)		pc/h/ln
S		mph
D = v_p / S		pc/mi/ln
Required Number of Lanes, N		

Glossary

N - Number of lanes
V - Hourly volume
v_p - Flow rate
LOS - Level of service
S - Speed
D - Density
FFS - Free-flow speed
BFFS - Base free-flow speed
DDHV - Directional design hour volume

Factor Location

E_R - Exhibits 11-10, 11-12
E_T - Exhibits 11-10, 11-11, 11-13
f_p - Page 11-18
LOS, S, FFS, v_p - Exhibits 11-2, 11-3
f_{LW} - Exhibit 11-8
f_{LC} - Exhibit 11-9
TRD - Page 11-11

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 4:11 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*I-405 NB*
Agency or Company	*LLG*	From/To	*Woodruff Ave/Palo Verde Ave*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*PM Peak Hour*	Analysis Year	*Year 2019 Plus Project*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*8146*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length Up/Down %	*mi*

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs

Lane Width		ft
Rt-Side Lat. Clearance		ft
Number of Lanes, N	*6*	
Total Ramp Density, TRD		ramps/mi
FFS (measured)	*65.0*	mph
Base free-flow Speed, BFFS		mph

Calc Speed Adj and FFS

f_{LW}		mph
f_{LC}		mph
TRD Adjustment		mph
FFS	*65.0*	mph

LOS and Performance Measures

Operational (LOS)

v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*1443*	pc/h/ln
S	*65.0*	mph
D = v_p / S	*22.2*	pc/mi/ln
LOS	*C*	

Design (N)

Design (N)

Design LOS		
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)		pc/h/ln
S		mph
D = v_p / S		pc/mi/ln
Required Number of Lanes, N		

Glossary

N - Number of lanes
V - Hourly volume
v_p - Flow rate
LOS - Level of service
S - Speed
D - Density
FFS - Free-flow speed
BFFS - Base free-flow speed
DDHV - Directional design hour volume

Factor Location

E_R - Exhibits 11-10, 11-12
E_T - Exhibits 11-10, 11-11, 11-13
f_p - Page 11-18
LOS, S, FFS, v_p - Exhibits 11-2, 11-3
f_{LW} - Exhibit 11-8
f_{LC} - Exhibit 11-9
TRD - Page 11-11

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 4:11 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*I-405 NB*
Agency or Company	*LLG*	From/To	*Palo Verde Ave/Studebaker Rd*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*PM Peak Hour*	Analysis Year	*Year 2019 Plus Project*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*8462*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length Up/Down %	*mi*

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs

Lane Width		ft
Rt-Side Lat. Clearance		ft
Number of Lanes, N	*6*	
Total Ramp Density, TRD		ramps/mi
FFS (measured)	*65.0*	mph
Base free-flow Speed, BFFS		mph

Calc Speed Adj and FFS

f_{LW}		mph
f_{LC}		mph
TRD Adjustment		mph
FFS	*65.0*	mph

LOS and Performance Measures

Operational (LOS)

v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*1499*	pc/h/ln
S	*64.9*	mph
D = v_p / S	*23.1*	pc/mi/ln
LOS	*C*	

Design (N)

Design (N)

Design LOS	
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	pc/h/ln
S	mph
D = v_p / S	pc/mi/ln
Required Number of Lanes, N	

Glossary

N - Number of lanes
V - Hourly volume
v_p - Flow rate
LOS - Level of service
S - Speed
D - Density
FFS - Free-flow speed
BFFS - Base free-flow speed
DDHV - Directional design hour volume

Factor Location

E_R - Exhibits 11-10, 11-12
E_T - Exhibits 11-10, 11-11, 11-13
f_p - Page 11-18
LOS, S, FFS, v_p - Exhibits 11-2, 11-3
f_{LW} - Exhibit 11-8
f_{LC} - Exhibit 11-9
TRD - Page 11-11

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 4:11 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*I-405 NB*
Agency or Company	*LLG*	From/To	*South of Studebaker Rd*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*PM Peak Hour*	Analysis Year	*Year 2019 Plus Project*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*8272*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length Up/Down %	*mi*

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs

Lane Width		ft
Rt-Side Lat. Clearance		ft
Number of Lanes, N	*5*	
Total Ramp Density, TRD		ramps/mi
FFS (measured)	*65.0*	mph
Base free-flow Speed, BFFS		mph

Calc Speed Adj and FFS

f_{LW}		mph
f_{LC}		mph
TRD Adjustment		mph
FFS	*65.0*	mph

LOS and Performance Measures

Operational (LOS)

v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*1759*	pc/h/ln
S	*63.2*	mph
D = v_p / S	*27.8*	pc/mi/ln
LOS	*D*	

Design (N)

Design (N)

Design LOS		
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)		pc/h/ln
S		mph
D = v_p / S		pc/mi/ln
Required Number of Lanes, N		

Glossary

N - Number of lanes
V - Hourly volume
v_p - Flow rate
LOS - Level of service
S - Speed
D - Density
FFS - Free-flow speed
BFFS - Base free-flow speed
DDHV - Directional design hour volume

Factor Location

E_R - Exhibits 11-10, 11-12
E_T - Exhibits 11-10, 11-11, 11-13
f_p - Page 11-18
LOS, S, FFS, v_p - Exhibits 11-2, 11-3
f_{LW} - Exhibit 11-8
f_{LC} - Exhibit 11-9
TRD - Page 11-11

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 4:11 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*I-405 SB*
Agency or Company	*LLG*	From/To	*Bellflower Blvd/Woodruff Ave*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*PM Peak Hour*	Analysis Year	*Year 2019 Plus Project*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*10385*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length Up/Down %	*mi*

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs

Lane Width		ft
Rt-Side Lat. Clearance		ft
Number of Lanes, N	*6*	
Total Ramp Density, TRD		ramps/mi
FFS (measured)	*65.0*	mph
Base free-flow Speed, BFFS		mph

Calc Speed Adj and FFS

f_{LW}		mph
f_{LC}		mph
TRD Adjustment		mph
FFS	*65.0*	mph

LOS and Performance Measures

Operational (LOS)

v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*1840*	pc/h/ln
S	*62.3*	mph
D = v_p / S	*29.6*	pc/mi/ln
LOS	*D*	

Design (N)

Design (N)

Design LOS		
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)		pc/h/ln
S		mph
D = v_p / S		pc/mi/ln
Required Number of Lanes, N		

Glossary

N - Number of lanes
V - Hourly volume
v_p - Flow rate
LOS - Level of service
S - Speed
D - Density
FFS - Free-flow speed
BFFS - Base free-flow speed
DDHV - Directional design hour volume

Factor Location

E_R - Exhibits 11-10, 11-12
E_T - Exhibits 11-10, 11-11, 11-13
f_p - Page 11-18
LOS, S, FFS, v_p - Exhibits 11-2, 11-3
f_{LW} - Exhibit 11-8
f_{LC} - Exhibit 11-9
TRD - Page 11-11

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 4:12 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*I-405 SB*
Agency or Company	*LLG*	From/To	*Woodruff Ave/Palo Verde Ave*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*PM Peak Hour*	Analysis Year	*Year 2019 Plus Project*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*10187*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length	*mi*
			Up/Down %	

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs

Lane Width		ft
Rt-Side Lat. Clearance		ft
Number of Lanes, N	*5*	
Total Ramp Density, TRD		ramps/mi
FFS (measured)	*65.0*	mph
Base free-flow Speed, BFFS		mph

Calc Speed Adj and FFS

f_{LW}		mph
f_{LC}		mph
TRD Adjustment		mph
FFS	*65.0*	mph

LOS and Performance Measures

Operational (LOS)

v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*2166*	pc/h/ln
S	*56.7*	mph
D = v_p / S	*38.2*	pc/mi/ln
LOS	*E*	

Design (N)

Design (N)

Design LOS	
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	pc/h/ln
S	mph
D = v_p / S	pc/mi/ln
Required Number of Lanes, N	

Glossary

N - Number of lanes
V - Hourly volume
v_p - Flow rate
LOS - Level of service
S - Speed
D - Density
FFS - Free-flow speed
BFFS - Base free-flow speed
DDHV - Directional design hour volume

Factor Location

E_R - Exhibits 11-10, 11-12
E_T - Exhibits 11-10, 11-11, 11-13
f_p - Page 11-18
LOS, S, FFS, v_p - Exhibits 11-2, 11-3
f_{LW} - Exhibit 11-8
f_{LC} - Exhibit 11-9
TRD - Page 11-11

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 4:12 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*I-405 SB*
Agency or Company	*LLG*	From/To	*Palo Verde Ave/Studebaker Rd*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*PM Peak Hour*	Analysis Year	*Year 2019 Plus Project*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*10584*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length	*mi*
			Up/Down %	

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs

Lane Width		ft
Rt-Side Lat. Clearance		ft
Number of Lanes, N	*6*	
Total Ramp Density, TRD		ramps/mi
FFS (measured)	*65.0*	mph
Base free-flow Speed, BFFS		mph

Calc Speed Adj and FFS

f_{LW}		mph
f_{LC}		mph
TRD Adjustment		mph
FFS	*65.0*	mph

LOS and Performance Measures

Operational (LOS)

v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*1875*	pc/h/ln
S	*61.8*	mph
D = v_p / S	*30.3*	pc/mi/ln
LOS	*D*	

Design (N)

Design (N)

Design LOS		
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)		pc/h/ln
S		mph
D = v_p / S		pc/mi/ln
Required Number of Lanes, N		

Glossary

N - Number of lanes	S - Speed
V - Hourly volume	D - Density
v_p - Flow rate	FFS - Free-flow speed
LOS - Level of service	BFFS - Base free-flow speed
DDHV - Directional design hour volume	

Factor Location

E_R - Exhibits 11-10, 11-12	f_{LW} - Exhibit 11-8
E_T - Exhibits 11-10, 11-11, 11-13	f_{LC} - Exhibit 11-9
f_p - Page 11-18	TRD - Page 11-11
LOS, S, FFS, v_p - Exhibits 11-2, 11-3	

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 4:12 PM

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst	*ML*	Highway/Direction of Travel	*I-405 SB*
Agency or Company	*LLG*	From/To	*South of Studebaker Rd*
Date Performed	*1/18/17*	Jurisdiction	
Analysis Time Period	*PM Peak Hour*	Analysis Year	*Year 2019 Plus Project*

Project Description *2-16-3779 2nd & PCH Project, Long Beach*

☑ Oper.(LOS) ☐ Des.(N) ☐ Planning Data

Flow Inputs

Volume, V	*10346*	veh/h	Peak-Hour Factor, PHF	*0.95*
AADT		veh/day	%Trucks and Buses, P_T	*2*
Peak-Hr Prop. of AADT, K			%RVs, P_R	*0*
Peak-Hr Direction Prop, D			General Terrain:	*Level*
DDHV = AADT x K x D		veh/h	Grade % Length	*mi*
			Up/Down %	

Calculate Flow Adjustments

f_p	*1.00*	E_R	*1.2*
E_T	*1.5*	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	*0.990*

Speed Inputs			Calc Speed Adj and FFS		
Lane Width		ft			
Rt-Side Lat. Clearance		ft	f_{LW}		mph
Number of Lanes, N	*6*		f_{LC}		mph
Total Ramp Density, TRD		ramps/mi	TRD Adjustment		mph
FFS (measured)	*65.0*	mph	FFS	*65.0*	mph
Base free-flow Speed, BFFS		mph			

LOS and Performance Measures			Design (N)	
Operational (LOS)			Design (N)	
v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	*1833*	pc/h/ln	Design LOS	
			v_p = (V or DDHV) / (PHF x N x f_{HV} x f_p)	pc/h/ln
S	*62.3*	mph	S	mph
D = v_p / S	*29.4*	pc/mi/ln	D = v_p / S	pc/mi/ln
LOS	*D*		Required Number of Lanes, N	

Glossary		Factor Location	
N - Number of lanes	S - Speed	E_R - Exhibits 11-10, 11-12	f_{LW} - Exhibit 11-8
V - Hourly volume	D - Density	E_T - Exhibits 11-10, 11-11, 11-13	f_{LC} - Exhibit 11-9
v_p - Flow rate	FFS - Free-flow speed	f_p - Page 11-18	TRD - Page 11-11
LOS - Level of service	BFFS - Base free-flow speed	LOS, S, FFS, v_p - Exhibits 11-2, 11-3	
DDHV - Directional design hour volume			

Copyright © 2016 University of Florida, All Rights Reserved *HCS 2010*™ Version 6.80 Generated: 1/18/2017 4:13 PM